

Annex B

# Environmental Mitigation Implementation Schedule

## Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension

**Note:** Chapters 1 to 2 of the EIA report present the background information of the Project, identified concurrent projects, objectives and scope for various environmental aspects, and description on alternative options and construction description. Chapters 3 to 12 of the EIA report present the EIA findings and mitigation measures are described below with cross-reference to the EIA report. Chapters 13 to 15 describe the environmental monitoring requirements, summary of environmental outcomes and conclusion.

| EIA Ref.  | EM&A Log Ref | Recommended Mitigation Measures   | Objectives of the Recommended Measures & Main Concerns to address | Implementation Agent | Location / Timing      | Implementation Stage | Requirements and / or standards to be achieved  |
|---|--------------|---|---|----------------------|------------------------|----------------------|---|
| <i>Common Mitigation Measures (Applicable to ALL Project Components, including DPs and Non-DPs)</i> |              |   |   |                      |                        |                      |   |
| <i>Construction Dust Impact</i>   |              |   |   |                      |                        |                      |   |
| S3.4.6  | D1           | Water spraying every hour on exposed worksites and haul road.   | Minimize dust impact at the nearby sensitive receivers            | Contractor           | All construction sites | Construction stage   | <ul style="list-style-type: none"> <li>• APCO</li> <li>• To control the dust impact to meet HKAQO and TM-EIAO criteria</li> </ul> |
| S3.4.6  | D2           | The contractor shall follow the procedures and requirements given in the Air Pollution Control (Construction Dust) Regulation   | Minimize dust impact at the nearby sensitive receivers            | Contractor           | All construction sites | Construction stage   | <ul style="list-style-type: none"> <li>• APCO</li> <li>• To control the dust impact to meet HKAQO and TM-EIAO criteria</li> </ul> |
| S3.4.6  | D3           | <p>The following dust suppression measures should be incorporated to control the dust nuisance throughout the construction phase:</p> <ul style="list-style-type: none"> <li>• Any excavated or stockpile of dusty material should be covered entirely by impervious sheeting or sprayed with water to maintain the entire surface wet and then removed or backfilled or reinstated where practicable within 24 hours of the excavation or unloading;</li> <li>• Any dusty materials remaining after a stockpile is removed should be wetted with water and cleared from the surface of roads;</li> </ul> | Minimize dust impact at the nearby sensitive receivers            | Contractor           | All construction sites | Construction stage   | <ul style="list-style-type: none"> <li>• APCO</li> <li>• To control the dust impact to meet HKAQO and TM-EIAO criteria</li> </ul> |

### Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension

| EIA Ref. | EM&A Log Ref | Recommended Mitigation Measures  | Objectives of the Recommended Measures & Main Concerns to address | Implementation Agent | Location / Timing | Implementation Stage | Requirements and / or standards to be achieved |
|----------|--------------|--|---|----------------------|-------------------|----------------------|--|
|          |              | <ul style="list-style-type: none"> <li>• A stockpile of dusty material should not be extended beyond the pedestrian barriers, fencing or traffic cones;</li> <li>• The load of dusty materials on a vehicle leaving a construction site should be covered entirely by impervious sheeting to ensure that the dusty materials do not leak from the vehicle;</li> <li>• Where practicable, vehicle washing facilities with high pressure water jet should be provided at every discernible or designated vehicle exit point. The area where vehicle washing takes place and the road section between the washing facilities and the exit point should be paved with concrete, bituminous materials or hardcores;</li> <li>• When there are open excavation and reinstatement works, hoarding of not less than 2.4m high should be provided as far as practicable along the site boundary with provision for public crossing. Good site practice shall also be adopted by the Contractor to ensure the conditions of the hoardings are properly maintained throughout the construction period;</li> <li>• The portion of any road leading only to construction site that is within 30m of a vehicle entrance or exit should be kept clear of dusty materials;</li> <li>• Surfaces where any pneumatic or power-driven drilling, cutting, polishing or other mechanical breaking operation takes place should be sprayed with water or a dust suppression chemical continuously;</li> <li>• Any area that involves demolition activities should be sprayed with water or a dust suppression chemical immediately prior to, during and immediately after the activities so as to maintain the entire surface wet;</li> <li>• Where a scaffolding is erected around the perimeter of a building under construction, effective dust screens,</li> </ul> |   |                      |                   |                      |  |

**Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension**

| EIA Ref. | EM&A Log Ref | Recommended Mitigation Measures  | Objectives of the Recommended Measures & Main Concerns to address | Implementation Agent | Location / Timing                 | Implementation Stage | Requirements and / or standards to be achieved              |
|----------|--------------|--|---|----------------------|-----------------------------------|----------------------|---|
|          |              | <p>sheeting or netting should be provided to enclose the scaffolding from the ground floor level of the building, or a canopy should be provided from the first floor level up to the highest level of the scaffolding;</p> <ul style="list-style-type: none"> <li>• Any skip hoist for material transport should be totally enclosed by impervious sheeting;</li> <li>• Every stock of more than 20 bags of cement or dry pulverised fuel ash (PFA) should be covered entirely by impervious sheeting or placed in an area sheltered on the top and the 3 sides;</li> <li>• Cement or dry PFA delivered in bulk should be stored in a closed silo fitted with an audible high level alarm which is interlocked with the material filling line and no overfilling is allowed;</li> <li>• Loading, unloading, transfer, handling or storage of bulk cement or dry PFA should be carried out in a totally enclosed system or facility, and any vent or exhaust should be fitted with an effective fabric filter or equivalent air pollution control system; and</li> <li>• Exposed earth should be properly treated by compaction, turfing, hydroseeding, vegetation planting or sealing with latex, vinyl, bitumen, shortcrete or other suitable surface stabiliser within six months after the last construction activity on the construction site or part of the construction site where the exposed earth lies.</li> </ul> |   |                      |                                   |                      |   |
| S3.4.6   | D4           | Implement regular dust monitoring under EM&A programme during the construction stage.  | Monitoring of dust impact   | Contractor           | Selected dust monitoring stations | Construction stage   | <ul style="list-style-type: none"> <li>• TM-EIAO</li> </ul> |

### Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension

| EIA Ref.                  | EM&A Log Ref | Recommended Mitigation Measures  | Objectives of the Recommended Measures & Main Concerns to address | Implementation Agent | Location / Timing                        | Implementation Stage | Requirements and / or standards to be achieved |
|---------------------------|--------------|--|---|----------------------|--|----------------------|--|
| <b>Construction Noise</b> |              |  |   |                      |  |                      |  |
| S4.3.4                    | N1           | Implement the following good site management practices: <ul style="list-style-type: none"> <li>• only well-maintained plant should be operated on-site and plant should be serviced regularly during the construction programme;</li> <li>• machines and plant (such as trucks, cranes) that may be in intermittent use should be shut down between work periods or should be throttled down to a minimum;</li> <li>• plant known to emit noise strongly in one direction, where possible, be orientated so that the noise is directed away from nearby NSRs;</li> <li>• silencers or mufflers on construction equipment should be properly fitted and maintained during the construction works;</li> <li>• mobile plant should be sited as far away from NSRs as possible and practicable;</li> <li>• material stockpiles, site office and other structures should be effectively utilised, where practicable, to screen noise from on-site construction activities.</li> </ul> | Control construction airborne noise                               | Contractor           | All construction sites where practicable | Construction stage   | • Annex 5, TM-EIAO                             |
| S4.3.4                    | N2           | Use of quiet plant which should be made reference to the Powered Mechanical Equipment (PME) listed in the Technical Memorandum or the Quality Powered Mechanical Equipment (QPME) / other commonly used PME listed in Environmental Protection Department (EPD) web pages as far as possible which includes the Sound Power Level (SWLs) for specific quiet PME.   | Reduce the noise levels of plant items                            | Contractor           | All construction sites where practicable | Construction stage   | • Annex 5, TM-EIAO                             |
| S4.3.4                    | N3           | Install movable temporary noise barriers (typical design is wooden framed barrier with a small-cantilevered upper portion of superficial density no less than 7kg/m <sup>2</sup> on a skid   | Screen the noisy plant items to be used at all                    | Contractor           | All construction sites where             | Construction stage   | • Annex 5, TM-EIAO                             |

**Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension**

| <b>EIA Ref.</b>                                      | <b>EM&amp;A Log Ref</b> | <b>Recommended Mitigation Measures</b>  | <b>Objectives of the Recommended Measures &amp; Main Concerns to address</b>   | <b>Implementation Agent</b>                          | <b>Location / Timing</b>   | <b>Implementation Stage</b>  | <b>Requirements and / or standards to be achieved</b> |
|--|-------------------------|---|--|--|--|--|---|
|  |                         | footing with 25mm thick internal sound absorptive lining), and full enclosure, screen the noisy plants including air compressors, generators etc.   | construction sites   |  | practicable  |  |   |
| S4.3.4   | N4                      | Implement a noise monitoring under EM&A programme.  | Monitor the construction noise levels at the selected representative locations | Contractor   | Selected noise monitoring stations   | Construction stage   | • TM-EIAO   |
| <b><i>Operational Noise (Road Traffic Noise)</i></b> |                         |   |  |  |  |  |   |
| S4.5.4   | N5                      | <p>Provide a series of noise mitigation measures including low noise surfacing material, noise barriers, facades with no openable window, school boundary walls and architectural fins before occupation of the protected NSRs. Locations of noise mitigation measures are stated as following:</p> <p>Year 2023:</p> <ul style="list-style-type: none"> <li>• Facade with no openable window at B1-1 and B1-2 for TCE; TCV-6 for TCW</li> <li>• 1.5m long architectural fin at B1-1 and B1-2 for TCE</li> <li>• Approx. 50m long, 4m high school boundary wall at possible school development near Tung Chung Area 39</li> <li>• Approx. 120m long, 5m high vertical barrier with 3m cantilevered arm at 45° at the corner at junction between Chung Mun Road and Road L24</li> <li>• Approx. 210m long LNRS along Chung Mun Road</li> <li>• Approx. 160m long LNRS along Road L24</li> <li>• Approx. 160m long LNRS along Road L30</li> </ul> <p>Year 2025:</p> <ul style="list-style-type: none"> <li>• Facade with no openable window at B1-1, B1-2, D1-1,</li> </ul> | Reduce operation noise from road traffic                                       | Relevant government departments / Private developers | Refer to Figure 6.1, Figure 6.1a-b, Figure 6.2, Figures 6.2a-b, Figure 6.3, Figures 6.3a-d, Figure 6.4, and Figures 6.4a-e | Prior to operation of the Project for existing NSRs. While for mitigation measures to protect planned NSRs, it should be constructed before population intake of planned NSRs. | • TM-EIAO   |

**Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension**

| EIA Ref. | EM&A Log Ref | Recommended Mitigation Measures   | Objectives of the Recommended Measures & Main Concerns to address | Implementation Agent | Location / Timing | Implementation Stage | Requirements and / or standards to be achieved |
|----------|--------------|---|---|----------------------|-------------------|----------------------|--|
|          |              | <p>D1-2, D2-3 and D2-4 for TCE; TCV-6 for TCW</p> <ul style="list-style-type: none"> <li>• 1.5m long architectural fin at B1-1, B1-2 and D2-4 for TCE; TCV-1 for TCW</li> <li>• Approx. 60m long, 5m high school boundary wall along Road L3</li> <li>• Approx. 70m long, 5m high school boundary wall with 3m cantilevered arm at 45° along Road L3</li> <li>• Approx. 50m long, 4m high school boundary wall at possible school development near Tung Chung Area 39</li> <li>• Approx. 120m long, 5m high vertical barrier with 3m cantilevered arm at 45° at the corner at junction between Chung Mun Road and Road L24</li> <li>• Approx. 210m long LNRS along Chung Mun Road</li> <li>• Approx. 160m long LNRS along Road L24</li> <li>• Approx. 160m long LNRS along Road L30</li> </ul> <p>Year 2027:</p> <ul style="list-style-type: none"> <li>• Facade with no openable window at A1-1, A1-2, A2-1, A2-2, A2-3, A2-4, B1-1, B1-2, D1-1, D1-2, D2-3 and D2-4 for TCE; TCV-6 for TCW</li> <li>• 1.5m long architectural fin at A2-1, A2-4, B1-1, B1-2 and D2-4 for TCE;</li> <li>• 1.8m long architectural fin at A1-1, A1-2, A2-1 and A2-4</li> <li>• Approx. 60m long, 5m high school boundary wall along Road L3</li> <li>• Approx. 70m long, 5m high school boundary wall with 3m cantilevered arm at 45° along Road L3</li> <li>• Approx. 50m long, 4m high school boundary wall at</li> </ul> |   |                      |                   |                      |  |

**Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension**

| <b>EIA Ref.</b> | <b>EM&amp;A Log Ref</b> | <b>Recommended Mitigation Measures</b>   | <b>Objectives of the Recommended Measures &amp; Main Concerns to address</b> | <b>Implementation Agent</b> | <b>Location / Timing</b> | <b>Implementation Stage</b> | <b>Requirements and / or standards to be achieved</b> |
|-----------------|-------------------------|--|--|-----------------------------|--------------------------|-----------------------------|---|
|                 |                         | <p>possible school development near Tung Chung Area 39</p> <ul style="list-style-type: none"> <li>• Approx. 120m long, 5m high vertical barrier with 3m cantilevered arm at 45° at the corner at junction between Chung Mun Road and Road L24</li> <li>• Approx. 210m long LNRS along Chung Mun Road</li> <li>• Approx. 160m long LNRS along Road L24</li> <li>• Approx. 160m long LNRS along Road L30</li> </ul> <p>Year 2045:</p> <ul style="list-style-type: none"> <li>• Facade with no openable window at A1-1, A1-2, A2-1, A2-2, A2-3, A2-4, B1-1, B1-2, C1-1, C2-1, C2-2, D1-1, D1-2, D2-3, D2-4, E1-4 and E1-5 for TCE; TCV-1 and TCV-6 for TCW</li> <li>• 1.5m long architectural fin at A2-1, A2-4, B1-1, B1-2, C1-1 and D2-4 for TCE; TCV-1 for TCW</li> <li>• 1.8m long architectural fin at A1-1, A1-2, A2-1, A2-4 and C1-1</li> <li>• Approx. 100m long, 5m high absorptive vertical barrier along Road D3</li> <li>• Approx. 50m long, 5m high absorptive vertical barrier with 3m cantilevered arm at 45° along Road L7</li> <li>• Approx. 60m long, 5m high school boundary wall along Road L3</li> <li>• Approx. 70m long, 5m high school boundary wall with 3m cantilevered arm at 45° along Road L3</li> <li>• Approx. 80m long, 4m high school boundary wall along Road L2</li> <li>• Approx. 40m long, 3m high school boundary wall along Road L2</li> </ul> |  |                             |                          |                             |   |



**Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension**

| EIA Ref.                                      | EM&A Log Ref | Recommended Mitigation Measures   | Objectives of the Recommended Measures & Main Concerns to address | Implementation Agent                              | Location / Timing                 | Implementation Stage              | Requirements and / or standards to be achieved  |
|---|--------------|---|---|---|-----------------------------------|-----------------------------------|---|
|   |              | <ul style="list-style-type: none"> <li>• Approx. 50m long, 4m high school boundary wall at possible school development near Tung Chung Area 39</li> <li>• Approx. 120m long, 5m high vertical barrier with 3m cantilevered arm at 45° at the corner at junction between Chung Mun Road and Road L24</li> <li>• Approx. 210m long LNRS along Chung Mun Road</li> <li>• Approx. 160m long LNRS along Road L24</li> <li>• Approx. 160m long LNRS along Road L30</li> </ul>   |   |   |                                   |                                   |   |
| <b><i>Operational Noise (Fixed Noise)</i></b> |              |   |   |   |                                   |                                   |   |
| S4.6.4  | N6           | <p>For existing and planned NSRs which are located near to the proposed noise sources, the following tentative noise mitigation measures are considered:</p> <ul style="list-style-type: none"> <li>• All the pumps should be enclosed inside building structures;</li> <li>• Proper selection of quiet plant to reduce the tonality at NSRs;</li> <li>• Installation of silencer / acoustic enclosure / acoustic louvers for the exhaust of ventilation system.</li> <li>• For underground train stations, sound attenuators with sufficient attenuations can be installed to the ventilation shafts.</li> <li>• Openings of ventilation system should be located away from NSRs.</li> </ul> | Reduce operation fixed noise                                      | Relevant government departments / Future Operator | All plant rooms where practicable | Prior to operation of the Project | <ul style="list-style-type: none"> <li>• Noise Control Ordinance and its TM, TM-EIAO</li> </ul> |
| <b><i>Operational Noise (Rail Noise)</i></b>  |              |   |   |   |                                   |                                   |   |

**Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension**

| <b>EIA Ref.</b> | <b>EM&amp;A Log Ref</b> | <b>Recommended Mitigation Measures</b>  | <b>Objectives of the Recommended Measures &amp; Main Concerns to address</b> | <b>Implementation Agent</b>                       | <b>Location / Timing</b>   | <b>Implementation Stage</b>      | <b>Requirements and / or standards to be achieved</b>   |
|-----------------|-------------------------|---|--|---|--|----------------------------------|---|
| S4.8.4          | N7                      | <p>Before Phase 1 is occupied:</p> <ul style="list-style-type: none"> <li>• Facade with no openable windows for residential block at B1-2</li> <li>• 1.5m long architectural fin at B1-2</li> </ul> <p>Before Phase 3 is occupied:</p> <p>It should be noted that Railway Stations at TCE and TCW and its associated railway system is a Designated Project under Item A.2 of Schedule 2 of TM-EIAO. Hence, the proposed mitigation measures are tentative for cumulative assessment purpose in this EIA and all the mitigation measures will be revised by the railway operator during their Schedule 2 EIA.</p> <ul style="list-style-type: none"> <li>• Approx. 325m long, semi enclosure along the tracks of Tung Chung Line facing B0-2 and COM-1</li> <li>• Approx. 210m long, semi enclosure along the tracks of Tung Chung Line facing A1-2 and C1-1</li> <li>• Approx. 390m long, semi enclosure along the track of Tung Chung Line to Tung Chung direction facing C1-1 to C2-1</li> <li>• Approx. 630m long, semi enclosure along the track of Tung Chung Line to Hong Kong direction facing C1-1 and C2-1</li> </ul> | Reduce operation rail noise  | Relevant government departments / Future Operator | Refer to Figure 6.1, Figure 6.1a-b, Figure 6.2, Figures 6.2a-b, Figure 6.3, Figures 6.3a-d, Figure 6.4, and Figures 6.4a-e | Prior to final population intake | <ul style="list-style-type: none"> <li>• Noise Control Ordinance and its TM, TM-EIAO</li> </ul> |

**Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension**

| EIA Ref.                                  | EM&A Log Ref | Recommended Mitigation Measures   | Objectives of the Recommended Measures & Main Concerns to address                                  | Implementation Agent | Location / Timing                       | Implementation Stage | Requirements and / or standards to be achieved   |
|---|--------------|---|--|----------------------|---|----------------------|--|
| <i>Water Quality (Construction Phase)</i> |              |   |  |                      |   |                      |  |
| S5.4.3                                    | W1           | <p><u>General Construction Activities</u></p> <p>In accordance with the Practice Note for Professional Persons on Construction Site Drainage, Environmental Protection Department, 1994 (ProPECC PN1/94), best management practices should be implemented on site as far as practicable. The best practices are detailed below:</p> <ul style="list-style-type: none"> <li>• At the start of site establishment, perimeter cut-off drains to direct off-site water around the site should be constructed with internal drainage works. Channels, earth bunds or sand bag barriers should be provided on site to direct stormwater to silt removal facilities.;</li> <li>• Diversion of natural stormwater should be provided as far as possible. The design of temporary on-site drainage should prevent runoff going through site surface, construction machinery and equipment in order to avoid or minimize polluted runoff. Sedimentation tanks with sufficient capacity, constructed from pre-formed individual cells of approximately 6 to 8 m3 capacities, are recommended as a general mitigation measure which can be used for settling surface runoff prior to disposal. The system capacity shall be flexible and able to handle multiple inputs from a variety of sources and suited to applications where the influent is pumped;</li> <li>• The dikes or embankments for flood protection should be implemented around the boundaries of earthwork areas. Temporary ditches should be provided to facilitate the runoff discharge into an appropriate watercourse, through a silt/sediment trap. The silt/sediment traps should be incorporated in the permanent drainage channels to enhance deposition rates;</li> <li>• The design of efficient silt removal facilities should be</li> </ul> | To minimize water quality impact from construction site runoff and general construction activities | Contractor           | All construction sites where applicable | Construction stage   | <ul style="list-style-type: none"> <li>• Water Pollution Control Ordinance</li> <li>• ProPECC PN1/94</li> <li>• TM-EIAO</li> <li>• TM-DSS</li> </ul> |

**Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension**

| EIA Ref. | EM&A Log Ref | Recommended Mitigation Measures   | Objectives of the Recommended Measures & Main Concerns to address | Implementation Agent | Location / Timing | Implementation Stage | Requirements and / or standards to be achieved |
|----------|--------------|---|---|----------------------|-------------------|----------------------|--|
|          |              | <p>based on the guidelines in Appendix A1 of ProPECC PN 1/94. The detailed design of the sand/silt traps should be undertaken by the contractor prior to the commencement of construction;</p> <ul style="list-style-type: none"> <li>• Construction works should be programmed to minimize surface excavation works during the rainy seasons (April to September). All exposed earth areas should be completed and vegetated as soon as possible after earthworks have been completed. If excavation of soil cannot be avoided during the rainy season, or at any time of year when rainstorms are likely, exposed slope surfaces should be covered by tarpaulin or other means;</li> <li>• All drainage facilities and erosion and sediment control structures should be regularly inspected and maintained to ensure proper and efficient operation at all times and particularly following rainstorms. Deposited silt and grit should be removed regularly and disposed of by spreading evenly over stable, vegetated areas;</li> <li>• If the excavation of trenches in wet periods is necessary, it should be dug and backfilled in short sections wherever practicable. Water pumped out from trenches or foundation excavations should be discharged into storm drains via silt removal facilities;</li> <li>• All open stockpiles of construction materials (for example, aggregates, sand and fill material) should be covered with tarpaulin or similar fabric during rainstorms. Measures should be taken to prevent the washing away of construction materials, soil, silt or debris into any drainage system;</li> <li>• Manholes (including newly constructed ones) should always be adequately covered and temporarily sealed so as to prevent silt, construction materials or debris being washed into the drainage system and storm runoff being</li> </ul> |   |                      |                   |                      |  |

**Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension**

| EIA Ref. | EM&A Log Ref | Recommended Mitigation Measures   | Objectives of the Recommended Measures & Main Concerns to address | Implementation Agent | Location / Timing | Implementation Stage | Requirements and / or standards to be achieved |
|----------|--------------|---|---|----------------------|-------------------|----------------------|--|
|          |              | <p>directed into foul sewers;</p> <ul style="list-style-type: none"> <li>• Precautions to be taken at any time of year when rainstorms are likely, actions to be taken when a rainstorm is imminent or forecasted, and actions to be taken during or after rainstorms are summarized in Appendix A2 of ProPECC PN 1/94. Particular attention should be paid to the control of silty surface runoff during storm events;</li> <li>• All vehicles and plant should be cleaned before leaving a construction site to ensure no earth, mud, debris and the like is deposited by them on roads. An adequately designed and sited wheel washing facilities should be provided at every construction site exit where practicable. Wash-water should have sand and silt settled out and removed at least on a weekly basis to ensure the continued efficiency of the process. The section of access road leading to, and exiting from, the wheel-wash bay to the public road should be paved with sufficient backfall toward the wheel-wash bay to prevent vehicle tracking of soil and silty water to public roads and drains;</li> <li>• Oil interceptors should be provided in the drainage system downstream of any oil/fuel pollution sources. The oil interceptors should be emptied and cleaned regularly to prevent the release of oil and grease into the storm water drainage system after accidental spillage. A bypass should be provided for the oil interceptors to prevent flushing during heavy rain;</li> <li>• Construction solid waste, debris and rubbish on site should be collected, handled and disposed of properly to avoid water quality impacts;</li> <li>• All fuel tanks and storage areas should be provided with locks and sited on sealed areas, within bunds of a capacity equal to 110% of the storage capacity of the largest tank to prevent spilled fuel oils from reaching water sensitive</li> </ul> |   |                      |                   |                      |  |

**Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension**

| <b>EIA Ref.</b> | <b>EM&amp;A Log Ref</b> | <b>Recommended Mitigation Measures</b>   | <b>Objectives of the Recommended Measures &amp; Main Concerns to address</b>                              | <b>Implementation Agent</b> | <b>Location / Timing</b>                 | <b>Implementation Stage</b> | <b>Requirements and / or standards to be achieved</b>   |
|-----------------|-------------------------|--|---|-----------------------------|--|-----------------------------|---|
|                 |                         | <p>receivers nearby;and</p> <ul style="list-style-type: none"> <li>Regular environmental audit on the construction site should be carried out in order to prevent any malpractices. Notices should be posted at conspicuous locations to remind the workers not to discharge any sewage or wastewater into the water bodies, mangroves and open sea.</li> </ul>  |   |                             |  |                             |   |
| S5.4.3          | W2                      | <p><u>Sewage from workforce</u></p> <ul style="list-style-type: none"> <li>Portable chemical toilets and sewage holding tanks are recommended for handling the construction sewage generated by the workforce. A licensed contractor should be employed to provide appropriate and adequate portable toilets and be responsible for appropriate disposal and maintenance;</li> <li>Notices should be posted at conspicuous locations to remind the workers not to discharge any sewage or wastewater into the nearby environment during the construction phase of the Project;</li> <li>Regular environmental audit on the construction site should be conducted in order to provide an effective control of any malpractices and achieve continual improvement of environmental performance on site.</li> </ul> | To minimize water quality from sewage effluent in construction phase                                      | Contractor                  | All construction sites where practicable | Construction stage          | <ul style="list-style-type: none"> <li>Water Pollution Control Ordinance</li> <li>TM-DSS</li> </ul> |
| S5.4.3          | W3                      | <p><u>Construction Works and Bridge Works near Tung Chung Stream</u></p> <ul style="list-style-type: none"> <li>Use precast structures or other similar approaches</li> </ul>  | To prevent any construction works in river and avoid any direct water quality impact to Tung Chung Stream | Contractor                  | All construction sites where practicable | Construction stage          | <ul style="list-style-type: none"> <li>ProPECC PN1/94</li> </ul>                                    |
| S5.4.3          | W4                      | <p><u>Construction Works of Sewage Pumping Stations</u></p> <ul style="list-style-type: none"> <li>A buffer zone of about 20m or about 30m will be zoned to</li> </ul>   | To avoid any direct water quality impact to Tung Chung Stream   | Contractor                  | All construction sites where             | Construction stage          | <ul style="list-style-type: none"> <li>ProPECC PN1/94</li> </ul>                                    |

**Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension**

| <b>EIA Ref.</b> | <b>EM&amp;A Log Ref</b> | <b>Recommended Mitigation Measures</b>  | <b>Objectives of the Recommended Measures &amp; Main Concerns to address</b> | <b>Implementation Agent</b> | <b>Location / Timing</b>                 | <b>Implementation Stage</b> | <b>Requirements and / or standards to be achieved</b> |
|-----------------|-------------------------|---|--|-----------------------------|--|-----------------------------|---|
|                 |                         | prevent any construction works near river.  |  |                             | practicable                              |                             |   |
| S5.4.3          | W5                      | <p><u>Construction Work of Fresh Water and Salt Water Reservoirs</u></p> <ul style="list-style-type: none"> <li>• Good site management as stipulated in ProPECC PN1/94 will be fully implemented to avoid polluted liquid or solid wastes from falling into the river waters or drainage.</li> </ul>  | To avoid water quality impact  | Contractor                  | All construction sites where practicable | Construction stage          | • ProPECC PN1/94                                      |
| S5.4.3          | W6                      | <p><u>Construction of Storm Water Management Facilities and Polder Scheme</u></p> <ul style="list-style-type: none"> <li>• Good site management as stipulated in ProPECC PN1/94 will be fully implemented to avoid polluted liquid or solid wastes from falling into the river waters or drainage.</li> </ul>   | To avoid any direct water quality impact to Tung Chung Stream                | Contractor                  | All construction sites where practicable | Construction stage          | • ProPECC PN1/94                                      |
| S5.4.3          | W7                      | <p><u>Groundwater and Runoff for Tunnel Works</u></p> <ul style="list-style-type: none"> <li>• Cut-and-Cover method for the underpass at Road D1 in Tung Chung East to minimise the intrusion of groundwater. Good site management as stipulated in ProPECC PN1/94 will be fully implemented to avoid polluted liquid or solid wastes from falling into the river waters or drainage.</li> </ul>  | To avoid water quality impact  | Contractor                  | All construction sites where practicable | Construction stage          | • ProPECC PN1/94                                      |
| S5.5.8          | W8                      | <p><u>Good Management Practice in Construction Phase</u></p> <p>The following good site management practices shall be adopted for the filling works:</p> <ul style="list-style-type: none"> <li>• Water quality monitoring shall be implemented to ensure effective control of water pollution and recommend additional mitigation measures required;</li> <li>• The decent speed of grabs shall be controlled to minimize the seabed impact and to reduce the volume of over-dredging;</li> <li>• A perimeter silt curtain shall be installed during the entire</li> </ul> | To avoid water quality impact  | Contractor                  | All construction sites where practicable | Construction stage          | • ProPECC PN1/94                                      |

**Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension**

| EIA Ref. | EM&A Log Ref | Recommended Mitigation Measures  | Objectives of the Recommended Measures & Main Concerns to address | Implementation Agent | Location / Timing                        | Implementation Stage | Requirements and / or standards to be achieved                               |
|----------|--------------|--|---|----------------------|--|----------------------|--|
|          |              | reclamation periods;<br><ul style="list-style-type: none"> <li>• Barges or hoppers shall not be filled to a level which will cause overflow of materials or pollution of water during loading or transportation;</li> <li>• Excess materials shall be cleaned from the decks and exposed fittings of barges before the vessels are moved;</li> <li>• Plants should not be operated with leaking pipes and any pipe leakages shall be repaired quickly;</li> <li>• Adequate freeboard shall be maintained on barges to reduce the likelihood of decks being washed by wave action;</li> <li>• All vessels should be sized so that adequate clearance is maintained between vessels and the seabed in all tide conditions, to ensure that undue turbidity is not generated by turbulence from vessel movement or propeller wash; and</li> <li>• The works shall not cause foam, oil, grease, litter or other objectionable matter to be present in the water within and adjacent to the works site.</li> </ul> |   |                      |  |                      |  |
| S5.5.8   | W9           | <ul style="list-style-type: none"> <li>• The recovered C&amp;D materials for filling would be ensured no floating or non-inert material by visual inspection, quality assurance, etc.</li> </ul>   | To avoid water quality impact                                     | Contractor           | All construction sites where practicable | Construction stage   | <ul style="list-style-type: none"> <li>• Waste Disposal Ordinance</li> </ul> |



**Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension**

| <b>EIA Ref.</b>                          | <b>EM&amp;A Log Ref</b> | <b>Recommended Mitigation Measures</b>   | <b>Objectives of the Recommended Measures &amp; Main Concerns to address</b>                       | <b>Implementation Agent</b> | <b>Location / Timing</b>                       | <b>Implementation Stage</b> | <b>Requirements and / or standards to be achieved</b> |
|--|-------------------------|--|--|-----------------------------|--|-----------------------------|---|
| <i>Water Quality (Operational Phase)</i> |                         |  |  |                             |  |                             |   |
| S5.6.10                                  | W10                     | <p>The following mitigation measures will be implemented to TCV East, North and West SPS, upgraded CMRSPS, proposed TCE West SPS and TCE East SPS</p> <ul style="list-style-type: none"> <li>• 100% standby pump capacity with spare pump of 50% pump capacity</li> <li>• Dual-feed power supply</li> <li>• Wet well storage providing up to 6-hours ADWF capacity (equivalent to about 4 hours of response time during peak flow condition); and</li> <li>• Emergency communication mechanism amongst relevant government departments.</li> </ul> | To prevent the impact due to the emergency discharge at TCW and TCE                                | DSD                         | Proposed Sewage Pumping Station at TCW and TCE | Operational Stage           | • DSD's Sewerage Manual                               |
| S5.6.10                                  | W11                     | <p>The following mitigation measures will be implemented to gravity sewers and rising mains</p> <ul style="list-style-type: none"> <li>• Adopt high density polyethylene (HDPE) pipe for proposed gravity sewers and rising mains.</li> <li>• Further protection on proposed rising mains with concrete surround will be provided to mitigate the risk of bursting.</li> </ul>   | To minimize the risk of bursting and hence bursting discharge from gravity sewers and rising mains | DSD                         | Proposed rising mains within TCE and TCW       | Operational Stage           | -   |
| S5.6.10                                  | W12                     | <p><u>Maintenance Dredging for the Proposed Marina</u></p> <p>Silt curtain should be deployed to reduce the sediment dispersion from the dredging inside the marina.</p>   | To reduce the sediment dispersion  | Future operator             | Proposed marina at TCE                         | Operational Stage           | -   |

**Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension**

| EIA Ref.  | EM&A Log Ref | Recommended Mitigation Measures   | Objectives of the Recommended Measures & Main Concerns to address | Implementation Agent | Location / Timing                      | Implementation Stage | Requirements and / or standards to be achieved |
|---|--------------|---|---|----------------------|--|----------------------|--|
| <i>Sewage and Sewerage Treatment Implications</i> |              |   |   |                      |  |                      |  |
| S6.5.4  | SS1          | <p><u>Emergency Discharge of Proposed TCV West SPS, TCV East SPS, TCV North SPS and Upgraded CMRSPS</u></p> <p>The following mitigation measures will be implemented to TCV East, North and West SPS, and upgraded CMRSPS:</p> <ul style="list-style-type: none"> <li>• 100% standby pumping capacity within each SPS, with spare pump up to 50% pumping capacity stockpiled in each SPS for any emergency use</li> <li>• Twin rising mains</li> <li>• Dual-feed power supply</li> <li>• Emergency storage facilities up to 6-hours ADWF capacity; and</li> <li>• Emergency communication mechanism amongst relevant government departments.</li> </ul> | To prevent the impact due to the emergency discharge at TCW       | DSD                  | Proposed Sewage Pumping Station at TCW | Operational stage    | N/A  |
| S6.5.4  | SS2          | <p><u>Emergency Discharge of Proposed TCE West SPS and TCE East SPS</u></p> <p>In order to minimize the impact due to the emergency discharge, the following precautionary measures shall be included in the design of sewage pumping station:</p> <ul style="list-style-type: none"> <li>• 100% standby pumping capacity within each SPS, with spare pump up to 50% pumping capacity stockpiled in each SPS for any emergency use</li> <li>• Twin rising mains</li> <li>• Dual-feed power supply</li> <li>• Emergency storage facilities up to 6-hours ADWF capacity; and</li> <li>• Emergency communication mechanism amongst relevant</li> </ul>     | To minimize the impact due to the emergency discharge at TCE      | DSD                  | Proposed Sewage Pumping Station at TCE | Operational stage    | N/A  |

**Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension**

| <b>EIA Ref.</b> | <b>EM&amp;A Log Ref</b> | <b>Recommended Mitigation Measures</b>   | <b>Objectives of the Recommended Measures &amp; Main Concerns to address</b>                       | <b>Implementation Agent</b> | <b>Location / Timing</b>                 | <b>Implementation Stage</b> | <b>Requirements and / or standards to be achieved</b> |
|-----------------|-------------------------|--|--|-----------------------------|--|-----------------------------|---|
|                 |                         | government departments.  |  |                             |  |                             |   |
| S6.5.4          | SS3                     | <p>The following mitigation measures will be implemented to prevent pipe bursting on Rising Mains within TCE and TCW:</p> <ul style="list-style-type: none"> <li>• Strong pipe – use HDPE pipe with welded joints</li> <li>• Concrete encasement – concrete surround all rising mains</li> </ul> | To minimize the risk of bursting and hence bursting discharge from gravity sewers and rising mains | DSD                         | Proposed rising mains within TCE and TCW | Operational stage           | N/A   |

**Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension**

| EIA Ref.                                     | EM&A Log Ref | Recommended Mitigation Measures   | Objectives of the Recommended Measures & Main Concerns to address | Implementation Agent | Location / Timing      | Implementation Stage | Requirements and / or standards to be achieved                               |
|--|--------------|---|---|----------------------|------------------------|----------------------|--|
| <b>Waste Management (Construction Waste)</b> |              |   |   |                      |                        |                      |  |
| S7.4.1                                       | WM1          | <p><u>Good Site Practices</u></p> <p>The following good site practices are recommended throughout the construction activities:</p> <ul style="list-style-type: none"> <li>• nomination of an approved personnel, such as a site manager, to be responsible for the implementation of good site practices, arrangements for collection and effective disposal to an appropriate facility, of all wastes generated at the site;</li> <li>• training of site personnel in site cleanliness, appropriate waste management procedures and concepts of waste reduction, reuse and recycling;</li> <li>• provision of sufficient waste disposal points and regular collection for disposal;</li> <li>• imposition of penalty system on Contractors' improper behaviours when illegal dumping and landfilling outside their respective construction sites, i.e. on nearby farmlands and riverbanks, are reported;</li> <li>• appropriate measures to minimise windblown litter and dust during transportation of waste by either covering trucks or by transporting wastes in enclosed containers;</li> <li>• regular cleaning and maintenance programme for drainage systems, sumps and oil interceptors; and</li> <li>• the contractor should prepare a Waste Management Plan (WMP) as part of the Environmental Management Plan (EMP) in accordance with the ETWB TC(W) No. 19/2005 for construction phase. The EMP should be submitted to the Engineer for approval. Mitigation measures proposed in the EIA Report and the EM&amp;A Manual should be adopted.</li> </ul> | Minimize waste generation during construction                     | Contractor           | All construction sites | Construction stage   | <ul style="list-style-type: none"> <li>• Waste Disposal Ordinance</li> </ul> |

**Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension**

| <b>EIA Ref.</b> | <b>EM&amp;A Log Ref</b> | <b>Recommended Mitigation Measures</b>   | <b>Objectives of the Recommended Measures &amp; Main Concerns to address</b>  | <b>Implementation Agent</b> | <b>Location / Timing</b> | <b>Implementation Stage</b> | <b>Requirements and / or standards to be achieved</b>   |
|-----------------|-------------------------|--|---|-----------------------------|--------------------------|-----------------------------|---|
| S7.4.1          | WM2                     | <p><u>Waste Reduction Measures</u></p> <p>Waste reduction is best achieved at the planning and design phase, as well as by ensuring the implementation of good site practices. The following recommendations are proposed to achieve reduction:</p> <ul style="list-style-type: none"> <li>• segregate and store different types of waste in different containers, skip or stockpiles to enhance reuse or recycling of materials and their proper disposal;</li> <li>• proper storage and site practices to minimize the potential for damage and contamination of construction materials;</li> <li>• plan and stock construction materials carefully to minimize amount of waste generated and avoid unnecessary generation of waste;</li> <li>• sort out demolition debris and excavated materials from demolition works to recover reusable/recyclable portions (i.e. soil, broken concrete, metal etc.);</li> <li>• provide training to workers on the importance of appropriate waste management procedures, including waste reduction, reuse and recycling.</li> </ul> | Reduce waste generation   | Contractor                  | All construction sites   | Construction stage          | <ul style="list-style-type: none"> <li>• Waste Disposal Ordinance</li> </ul>  |
| S7.4.1          | WM3                     | <p><u>Storage of Waste</u></p> <p>The following recommendation should be implemented to minimize the impacts:</p> <ul style="list-style-type: none"> <li>• waste such as soil should be handled and stored well to ensure secure containment; and</li> <li>• Depends on actual site activities, certain locations within the site area would be used for storage of waste to enhance reuse. However, there would not be any designated location for storage of waste, and the storage locations would need to be adjusted to suite actual site conditions;</li> </ul>  | Good site practice to minimize the waste generation and recycle the C&D materials as far as practicable so as to reduce the amount for final disposal | Contractor                  | All construction sites   | Construction stage          | <ul style="list-style-type: none"> <li>• Land (Miscellaneous Provisions) Ordinance</li> <li>• Waste Disposal Ordinance</li> <li>• ETWB TCW No. 19/2005</li> </ul> |

**Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension**

| <b>EIA Ref.</b> | <b>EM&amp;A Log Ref</b> | <b>Recommended Mitigation Measures</b>  | <b>Objectives of the Recommended Measures &amp; Main Concerns to address</b> | <b>Implementation Agent</b> | <b>Location / Timing</b> | <b>Implementation Stage</b> | <b>Requirements and / or standards to be achieved</b>  |
|-----------------|-------------------------|---|--|-----------------------------|--------------------------|-----------------------------|--|
| S7.4.1          | WM4                     | <p><u>Collection and Transportation of Waste</u></p> <p>The following recommendation should be implemented to minimize the impacts:</p> <ul style="list-style-type: none"> <li>• remove waste in timely manner;</li> <li>• employ the trucks with cover or enclosed containers for waste transportation;</li> <li>• obtain relevant waste disposal permits from the appropriate authorities; and</li> <li>• disposal of waste should be done at licensed waste disposal facilities.</li> </ul>  | Minimize waste impacts from storage  | Contractor                  | All construction sites   | Construction stage          | <ul style="list-style-type: none"> <li>• Waste Disposal Ordinance</li> </ul>   |
| S7.4.1          | WM5                     | <p><u>Excavated and C&amp;D Materials</u></p> <p>Wherever practicable, C&amp;D materials should be segregated from other wastes to avoid contamination and ensure acceptability at public fill reception facilities or reclamation sites. The following mitigation measures should be implemented in handling the excavated and C&amp;D materials:</p> <ul style="list-style-type: none"> <li>• maintain temporary stockpiles and reuse excavated fill material for backfilling;</li> <li>• carry out on-site sorting;</li> <li>• make provisions in the Contract documents to allow and promote the use of recycled aggregates where appropriate; and</li> <li>• implement a trip-ticket system for each works contract to ensure that the disposal of C&amp;D materials are properly documented and verified, so as to avoid the illegal dumping and landfilling of C&amp;D materials on farmlands/ riverbanks at TCW;</li> </ul> <p>The recommended C&amp;D materials handling should include:</p> | Minimize waste impacts from excavated and C&D materials                      | Contractor                  | All construction sites   | Construction Stage          | <ul style="list-style-type: none"> <li>• Land (Miscellaneous Provisions) Ordinance</li> <li>• Waste Disposal Ordinance</li> <li>• ETWB TCW No. 19/2005</li> <li>• Project Administrative Handbook for Civil Engineering Works, 2012 Edition</li> </ul> |

**Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension**

| <b>EIA Ref.</b> | <b>EM&amp;A Log Ref</b> | <b>Recommended Mitigation Measures</b>   | <b>Objectives of the Recommended Measures &amp; Main Concerns to address</b> | <b>Implementation Agent</b> | <b>Location / Timing</b>                | <b>Implementation Stage</b> | <b>Requirements and / or standards to be achieved</b>   |
|-----------------|-------------------------|--|--|-----------------------------|---|-----------------------------|---|
|                 |                         | <ul style="list-style-type: none"> <li>On-site sorting of C&amp;D materials</li> <li>Reuse of C&amp;D materials</li> <li>Use of Standard Formwork and Planning of Construction Materials purchasing</li> </ul>   |  |                             |   |                             |   |
| S7.4.1          | WM6                     | <p><u>Provision of Wheel Wash Facilities</u></p> <p>Wheel wash facilities have to be provided at the site entrance before the trucks leaving the works area. Dust disturbance due to the trucks transportation to the public road network could be minimized by such arrangement.</p>  | Minimize waste impacts from trucks transportation                            | Contractor                  | All construction sites                  | Construction Stage          | N/A   |
| S7.4.1          | WM7                     | <p><u>Excavated Contaminated Soil</u></p> <p>As a precaution, it is recommended that standard good site practice should be implemented during the construction phase to minimize any potential exposure to contaminated soils or groundwater.</p>  | Remediate contaminated soil  | Contractor                  | All construction sites where applicable | Construction stage          | <ul style="list-style-type: none"> <li>Practice Guide for Investigation and Remediation of Contaminated Land</li> </ul> |
| S7.4.1          | WM8                     | <p><u>Excavated Marine Sediments</u></p> <p>Reference has been made to the sediment testing results. Possible mitigation measures to handle the contaminated/uncontaminated sediment are summarized as follows.</p> <ul style="list-style-type: none"> <li>All construction plant and equipment shall be designed and maintained to minimise the risk of silt, sediments, contaminants or other pollutants being released into the water column or deposited in the locations other than designated location.</li> <li>All vessels shall be sized such that adequate draft is maintained between vessels and the sea bed at all states of the tide to ensure that undue turbidity is not generated by turbulence from vessel movement or propeller wash.</li> <li>Adequate freeboard shall be maintained on barges to</li> </ul> | Handle excavated sediment  | Contractor                  | All construction sites where applicable | Construction stage          | <ul style="list-style-type: none"> <li>ETWB-TCW 34/2002</li> </ul>  |

**Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension**

| <b>EIA Ref.</b> | <b>EM&amp;A Log Ref</b> | <b>Recommended Mitigation Measures</b>   | <b>Objectives of the Recommended Measures &amp; Main Concerns to address</b> | <b>Implementation Agent</b> | <b>Location / Timing</b>                | <b>Implementation Stage</b> | <b>Requirements and / or standards to be achieved</b> |
|-----------------|-------------------------|--|--|-----------------------------|---|-----------------------------|---|
|                 |                         | ensure that decks are not washed by wave action.   |  |                             |   |                             |   |
| S7.4.1          | WM9                     | <p><u>Dumping of excavated sediment</u></p> <ul style="list-style-type: none"> <li>Keep and produce logs and other records to demonstrate compliance and ensure journeys are consistent with designated locations</li> <li>Comply with the conditions in the dumping permit.</li> <li>All bottom dumping vessels (hopper barges) shall be fitted with tight fittings seals to their bottom openings to prevent leakage of material.</li> <li>The excavated sediment shall be placed into the disposal pit by bottom dumping.</li> <li>Contaminated marine mud shall be transported by split barge of not less than 750m<sup>3</sup> capacity and capable of rapid opening and discharge at the disposal site.</li> <li>Discharge shall be undertaken rapidly and the hoppers shall be closed immediately. Sediment adhering to the sides of the hopper shall not be washed out of the hopper and the hopper shall remain closed until the barge returns to the disposal site.</li> <li>For Type 3 special disposal treatment, sealing of contaminant with geosynthetic containment before dropping into designated mud pit. A geosynthetic containment method is a method whereby the sediments are sealed in geosynthetic containers and, the containers would be dropped into the designated contaminated mud pit where they would be covered by further mud disposal and later by the mud pit capping at the disposal site, thereby fulfilling the requirements for fully confined mud disposal.</li> </ul> | Handle excavated sediment  | Contractor                  | All construction sites where applicable | Construction stage          | • ETWB-TCW 34/2002                                    |
| S7.4.1          | WM10                    | <u>Chemical Waste</u>  | Control the chemical waste and ensure proper                                 | Contractor                  | All construction                        | Construction stage          | • Waste Disposal                                      |



**Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension**

| <b>EIA Ref.</b>                             | <b>EM&amp;A Log Ref</b> | <b>Recommended Mitigation Measures</b>  | <b>Objectives of the Recommended Measures &amp; Main Concerns to address</b>       | <b>Implementation Agent</b> | <b>Location / Timing</b>         | <b>Implementation Stage</b> | <b>Requirements and / or standards to be achieved</b>   |
|---|-------------------------|---|--|-----------------------------|----------------------------------|-----------------------------|---|
|   |                         | If chemical wastes are produced at the construction site, the Contractors should register with EPD as chemical waste producer. Chemical wastes should be stored in appropriate containers and collected by a licensed chemical waste collector. Chemical wastes (e.g. spent lubricant oil) should be recycled at an appropriate facility as far as possible, while the chemical waste that cannot be recycled should be disposed of at either the Chemical Waste Treatment Centre, or another licensed facility, in accordance with the Waste Disposal (Chemical Waste) (General) Regulation. | storage, handling and disposal.  |                             | sites                            |                             | (Chemical Waste) General Regulation<br><ul style="list-style-type: none"> <li>Code of Practice on the Packaging, Labelling and Storage of Chemical Waste</li> </ul> |
| S7.4.1                                      | WM11                    | <u>General Refuse</u> <ul style="list-style-type: none"> <li>General refuse should be stored in enclosed bins separately from construction and chemical wastes. Recycling bins should also be placed to encourage recycling.</li> <li>Preferably enclosed and covered areas should be provided for general refuse collection and routine cleaning for these areas should also be implemented to keep areas clean.</li> <li>A reputable waste collector should be employed to remove general refuse on a daily basis.</li> </ul>   | Minimize production of the general refuse and avoid odour, pest and litter impacts | Contractor                  | All construction sites           | Construction stage          | <ul style="list-style-type: none"> <li>Waste Disposal Ordinance</li> </ul>  |
| S7.4.1                                      | WM12                    | <u>Floating Refuse accumulated along the seawall</u><br>The floating refuse along seawall should be collected to avoid accumulation. In addition, proper seawall design should be employed, and regular checking and cleaning of floating refuse should be implemented.   | Control floating refuse and ensure proper disposal                                 | Contractor                  | Construction sites along seawall | Construction stage          | <ul style="list-style-type: none"> <li>Waste Disposal Ordinance</li> </ul>  |
| <b>Waste Management (Operational Waste)</b> |                         |   |  |                             |                                  |                             |   |
| S7.4.2                                      | WM13                    | <u>Illegal dumping and landfilling</u>  | Prevent waste from   | Relevant                    | All                              | Operational stage           |   |

**Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension**

| <b>EIA Ref.</b> | <b>EM&amp;A Log Ref</b> | <b>Recommended Mitigation Measures</b>  | <b>Objectives of the Recommended Measures &amp; Main Concerns to address</b> | <b>Implementation Agent</b>     | <b>Location / Timing</b> | <b>Implementation Stage</b> | <b>Requirements and / or standards to be achieved</b> |
|-----------------|-------------------------|---|--|---------------------------------|--------------------------|-----------------------------|---|
|                 |                         | As a Development Permission Area (DPA) plan will be issued by the Town Planning Board as a temporary measure before the formal Outline Zoning Plan (OZP) for Tung Chung New Town Extension is adopted, statutory right to guide and control the development and use of land would be authorised. Should there be illegal dumping and landfilling observed/ reported on nearby farmlands and riverbanks, the government authority should take all necessary actions including but not limited to prosecution to remediate the circumstances.   | illegal dumping and landfilling  | government departments          | construction sites       |                             |   |
| S7.4.2          | WM14                    | <p><u>Municipal Solid Waste</u></p> <ul style="list-style-type: none"> <li>• A reputable waste collector should be employed to remove general refuse on a daily basis.</li> <li>• A 4-bin recycling system for paper, metals, plastics and glass should be adopted together with a general refuse bin. They should be placed in prominent places to promote waste separation at source. All recyclable materials should be collected by recyclers.</li> </ul>   | Remove general refuse generated from the proposed development                | FEHD/ Relevant Operators        | All construction sites   | Operational stage           | • Waste Disposal Ordinance                            |
| S7.4.2          | WM15                    | <p><u>Chemical Waste</u></p> <ul style="list-style-type: none"> <li>• Localized chemical waste storage areas should be located close to the source of waste generation for temporary storage. Drum-type containers with proper labelling should be used to collect chemical wastes for storage at the designated areas.</li> <li>• A licensed collector should be employed for the chemical waste collection and the chemical wastes should be disposed at an appropriate facility, such as Chemical Waste Treatment Centre (CWTC) in Tsing Yi.</li> <li>• Collection receipts issued by the licensed collector showing the quantities and types of chemical waste taken off-site and details of the treatment facility should be kept for record.</li> </ul> | Reduce chemical waste due to waste handling                                  | Contractors/ Relevant Operators | All construction sites   | Operational stage           |   |

**Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension**

| <b>EIA Ref.</b> | <b>EM&amp;A Log Ref</b> | <b>Recommended Mitigation Measures</b>   | <b>Objectives of the Recommended Measures &amp; Main Concerns to address</b> | <b>Implementation Agent</b> | <b>Location / Timing</b> | <b>Implementation Stage</b> | <b>Requirements and / or standards to be achieved</b>                      |
|-----------------|-------------------------|--|--|-----------------------------|--------------------------|-----------------------------|--|
| S7.4.2          | WM16                    | <u>Floating Refuse accumulated along seawall</u> <ul style="list-style-type: none"> <li>The floating refuse along seawall should be collected to avoid accumulation.</li> </ul>                      | Control floating refuse and ensure proper disposal                           | MD                          | Along seawall            | Operational stage           | <ul style="list-style-type: none"> <li>Waste Disposal Ordinance</li> </ul> |
| S7.4.2          | WM17                    | <u>Floating Refuse inside Marina</u> <ul style="list-style-type: none"> <li>Floating refuse at the marina will be collected and disposed by the licensed waste collector and as required.</li> </ul> | Reduce floating refuse washing up onto marina by currents and wind           | Future operator             | Marina                   | Operational stage           | <ul style="list-style-type: none"> <li>Waste Disposal Ordinance</li> </ul> |

**Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension**

| EIA Ref.                  | EM&A Log Ref | Recommended Mitigation Measures   | Objectives of the Recommended Measures & Main Concerns to address               | Implementation Agent   | Location / Timing                                       | Implementation Stage            | Requirements and / or standards to be achieved   |
|---------------------------|--------------|---|---|--|---|---------------------------------|--|
| <i>Land Contamination</i> |              |   |   |  |   |                                 |  |
| S8.4.1                    | LC1          | Undertaking environmental Site Inspection (SI) for all potentially contaminated sites as listed in the Contamination Assessment Plan (CAP). | Verify the land contamination potential before the commencement of construction | Project Proponent / Detailed Design Consultant / Private developer | All potentially contaminated sites as listed in the CAP | Prior to the construction stage | <ul style="list-style-type: none"> <li>• Annex 19 of the TM-EIAO, Guidelines for Assessment of Impact On Sites of Cultural Heritage and Other Impacts (Section 3 : Potential Contaminated Land Issues);</li> <li>• Guidance Manual for Use of Risk-Based Remediation Goals (RBRGs) for Contaminated Land Management;</li> <li>• Guidance Notes for Contaminated Land Assessment and Remediation; and</li> <li>• Practice Guide for Investigation and Remediation of Contaminated Land</li> </ul> |

**Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension**

| <b>EIA Ref.</b> | <b>EM&amp;A Log Ref</b> | <b>Recommended Mitigation Measures</b>   | <b>Objectives of the Recommended Measures &amp; Main Concerns to address</b>                                | <b>Implementation Agent</b>  | <b>Location / Timing</b>  | <b>Implementation Stage</b>     | <b>Requirements and / or standards to be achieved</b>                                       |
|-----------------|-------------------------|--|---|--|---|---------------------------------|---|
|                 |                         |  |   |  |   |                                 | <ul style="list-style-type: none"> <li>Recommendations in Health Risk Assessment</li> </ul> |
| S8.4.2          | LC2                     | <p>Re-appraisal would be required for the surveyed sites, other remaining areas of the PDAs and the works areas for the associated infrastructures because the development of these sites/ areas would only commence a number of years later, which may allow changes in the land usage of these sites and may give rise to potential land contamination issues.</p> <p>The Project Proponent's appointed consultant would prepare a supplementary CAP presenting the findings of the re-appraisal and strategy of the recommended SI, if required, and submit to EPD for review and approval.</p> | To assess the latest site situation and identify any potential additional hot spots and contaminated sites. | Project Proponent / Detailed Design Consultant / Private developer | All the surveyed sites as listed in the CAP, other remaining areas of the PDAs and works areas for the associated infrastructures | Prior to the construction stage | Ditto   |
| S8.5            | LC3                     | After approval of the supplementary CAP and upon completion of the SI works, the PP should prepare and submit a Contamination Assessment Report (CAR) for all potentially contaminated sites listed in the CAP to EPD for agreement.   | Present the findings of SI and evaluate the level and extent of potential contamination                     | Project Proponent / Detailed Design Consultant / Private developer | All the surveyed sites as listed in the CAP, other remaining areas of the PDAs and works areas for the associated infrastructures | Prior to the construction stage | Ditto   |
| S.8.5           | LC4                     | Preparation and submission of Remediation Action Plan (RAP) to EPD for agreement if land contamination is confirmed.   | Recommend appropriate mitigation measures for the contaminated soil and groundwater identified in the       | Project Proponent / Detailed Design Consultant / Private developer | All the surveyed sites as listed in the CAP, other remaining  | Prior to the construction stage | Ditto   |

**Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension**

| <b>EIA Ref.</b> | <b>EM&amp;A Log Ref</b> | <b>Recommended Mitigation Measures</b>                                      | <b>Objectives of the Recommended Measures &amp; Main Concerns to address</b>   | <b>Implementation Agent</b>  | <b>Location / Timing</b>  | <b>Implementation Stage</b>     | <b>Requirements and / or standards to be achieved</b> |
|-----------------|-------------------------|---|--|--|---|---------------------------------|---|
|                 |                         |   | assessment if remediation is required  |  | areas of the PDAs and works areas for the associated infrastructures  |                                 |   |
| S.8.5           | LC5                     | Preparation and submission of Remediation Report (RR) to EPD for agreement. | Demonstrate that the decontamination work is adequate and is carried out in accordance with the endorsed CAR and RAP | Project Proponent / Detailed Design Consultant / Private developer | All the surveyed sites as listed in the CAP, other remaining areas of the PDAs and works areas for the associated infrastructures | Prior to the construction stage | Ditto   |

**Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension**

| <b>EIA Ref.</b>                | <b>EM&amp;A Log Ref</b> | <b>Recommended Mitigation Measures</b>  | <b>Objectives of the Recommended Measures &amp; Main Concerns to address</b>       | <b>Implementation Agent</b> | <b>Location / Timing</b>                                     | <b>Implementation Stage</b> | <b>Requirements and / or standards to be achieved</b> |
|--------------------------------|-------------------------|---|--|-----------------------------|--|-----------------------------|---|
| <i>Ecology ( Design Phase)</i> |                         |   |  |                             |  |                             |   |
| S9.8.1                         | EC1                     | Development under the Project have avoided all the recognised sites of conservation importance, including Country Parks,  | To protect the recognised sites of conservation importance and habitats inside     | PlanD                       | TCW  | RODP                        | • Not available                                       |
| S9.8.1                         | EC2                     | About 30m buffer zone at the two main branches and the joined outlet section of Tung Chung Stream; and about 20m buffer for the major tributary at Ngau Au of Tung Chung Stream   | To protect the Tung Chung Stream   | PlanD                       | Tung Chung Stream  | RODP                        | • Not available                                       |
| S9.8.2                         | EC3                     | Detailed designs should avoid the encroachment of important habitats (e.g. Fung Shui Wood) within the Project Site  | To protect the important habitats within Project Site                              | PlanD                       | TCW  | Design Phase                | • Not available                                       |
| S9.8.2                         | EC4                     | Detailed designs of noise barriers to prevent bird collision  | To prevent bird collision  | HyD                         | Noise barriers   | Design Phase                | • Guidelines on Design of Noise Barriers              |
| S9.8.2                         | EC5                     | Measures and suitable designs of sewage pumping stations to prevent emergency discharge accidents in TCE and TCW <ul style="list-style-type: none"> <li>• 100% standby pumping capacity within each SPS, with spare pump up to 50% pumping capacity stockpiled in each SPS for any emergency use</li> <li>• Twin rising mains</li> <li>• Dual-feed power supply</li> <li>• Emergency storage facilities up to 6-hours ADWF capacity; and</li> <li>• Emergency communication mechanism amongst relevant government departments.</li> </ul> | To protect the water bodies from impacts due to emergency discharge in TCE and TCW | DSD                         | Proposed and Upgraded Sewage pumping stations at TCE and TCW | Design Phase                | • DSD standards                                       |

**Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension**

| <b>EIA Ref.</b>                      | <b>EM&amp;A Log Ref</b> | <b>Recommended Mitigation Measures</b>     | <b>Objectives of the Recommended Measures &amp; Main Concerns to address</b>   | <b>Implementation Agent</b>  | <b>Location / Timing</b>  | <b>Implementation Stage</b>  | <b>Requirements and / or standards to be achieved</b>  |
|--------------------------------------|-------------------------|--|--|--|---|--|--|
| <i>Ecology ( Construction Phase)</i> |                         |  |  |  |   |  |  |
| S9.8.2                               | EC6                     | Adoption of non-dredged reclamation method | To maintain the marine water quality   | Contractor   | Reclamation area of TCE and Road P1   | Construction phase   | <ul style="list-style-type: none"> <li>• EIA</li> <li>• Contractual requirements</li> </ul>  |
| S9.8.3                               | EC7                     | Compensation woodland planting             | To compensate loss of woodland, fung shui wood and orchard   | Contractor   | Uphill of Sheung Lei Pai FSW and Tung Chung Road  | Construction phase   | <ul style="list-style-type: none"> <li>• EIA</li> <li>• Contractual requirements</li> </ul>  |
| S9.8.3                               | EC8                     | Planting of emergent plant                 | To provide habitats for this Jhora Scrub Hopper, and to compensate the loss of their habitats (wet abandoned agricultural land) in northern section of Fong Yuen | DSD / Contractor   | Inside the future River Park  | Construction phase   | <ul style="list-style-type: none"> <li>• EIA</li> <li>• Contractual requirements</li> </ul>  |
| S9.8.3                               | EC9                     | Capture-and-translocation exercise         | Minimize the potential impact to amphibian species of conservation importance including Romer's Tree Frog and Chinese Bullfrog due to site formation             | For public works, provided by the government departments responsible for the construction of those public works or the site formation works .<br>For TCV-1 and | Public works near the eastern branch of Tung Chung Stream, in particular 1) the River Park, 2) the Distributor Road along | Capture-and-translocation exercise before commencement of site formation | <ul style="list-style-type: none"> <li>• EIA</li> <li>• Contractual requirements</li> <li>• Explanatory statement of the OZP (for private lots)</li> </ul> |



**Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension**

| EIA Ref. | EM&A Log Ref | Recommended Mitigation Measures  | Objectives of the Recommended Measures & Main Concerns to address | Implementation Agent  | Location / Timing   | Implementation Stage  | Requirements and / or standards to be achieved   |
|----------|--------------|--|---|---|---|---|--|
|          |              |  |   | TCV-5, where the lands within mostly belong to private lots, the future project proponents of those private lots, via the established mechanism for land transaction application. | the eastern branch of Tung Chung Stream, 3) the road upgrade along the existing Shek Mun Kap Road, and 4) the attenuation and treatment ponds in TCV-k, TCV-e, TCV-l, TCV-c, and TCV-n.<br><br>Also be required in private lands in TCV-1 and TCV-5 |   |  |
| S9.8.3   | EC10         | Preservation and/or Transplantation of plant species of conservation importance and the following monitoring of preserved/transplanted plant individuals | Protection of plant species of conservation importance            | For public works, provided by the government departments responsible for the construction of those public works or the site formation works.                                      | Within construction sites<br><br>All areas for public works<br><br>Also be required in private lands  | For preservation and/or transplantation, before commencement of site formation. | <ul style="list-style-type: none"> <li>• EIA</li> <li>• Contractual requirements</li> <li>• Explanatory statement of the OZP (for private lots)</li> </ul> |

**Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension**

| <b>EIA Ref.</b> | <b>EM&amp;A Log Ref</b> | <b>Recommended Mitigation Measures</b>   | <b>Objectives of the Recommended Measures &amp; Main Concerns to address</b> | <b>Implementation Agent</b>   | <b>Location / Timing</b>  | <b>Implementation Stage</b>           | <b>Requirements and / or standards to be achieved</b>                                       |
|-----------------|-------------------------|--|--|---|---|---------------------------------------|---|
|                 |                         |  |  | For TCV-1, where the lands within mostly belong to private lots, the future project proponents of those private lots, via the established mechanism for land transaction application. | in TCV-1.   |                                       |   |
| S9.8.3          | EC11                    | Defining and maintaining construction site boundaries (including erection of site hoarding, fences etc.) | Screen construction disturbance to the nearby habitats                       | Contractor  | Along the boundary of construction sites and buffer zones of Tung Chung Streams, along the boundary of mature woodland and Fung Shui Wood, and along the boundary between TCV-6 and the middle section of Fong Yuen | Before commencement of site formation | <ul style="list-style-type: none"> <li>• EIA</li> <li>• Contractual requirements</li> </ul> |
| S9.8.3          | EC12                    | Protection of Tung Chung Stream  | Minimize the potential water pollution due to                                | Contractor  | Within construction   | Construction                          | <ul style="list-style-type: none"> <li>• EIA</li> </ul>                                     |

**Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension**

| <b>EIA Ref.</b> | <b>EM&amp;A Log Ref</b> | <b>Recommended Mitigation Measures</b>  | <b>Objectives of the Recommended Measures &amp; Main Concerns to address</b>          | <b>Implementation Agent</b> | <b>Location / Timing</b>  | <b>Implementation Stage</b>          | <b>Requirements and / or standards to be achieved</b>                                       |
|-----------------|-------------------------|---|---|-----------------------------|---|--------------------------------------|---|
|                 |                         |   | construction of road crossings or other works near Tung Chung Stream                  |                             | sites   | phase                                | <ul style="list-style-type: none"> <li>• Contractual requirements</li> </ul>                |
| S9.8.3          | EC13                    | Implementation of standard site practices   | Minimize the potential impact due to dust, noise and runoff during construction phase | Contractor                  | Within construction sites   | Construction phase                   | <ul style="list-style-type: none"> <li>• EIA</li> <li>• Contractual requirements</li> </ul> |
| S9.8.4          | EC14                    | Adopting Eco-shoreline design   | To mitigate the impact of the marine loss   | CEDD                        | Along future seawall  | Construction stage                   | <ul style="list-style-type: none"> <li>• EIA</li> <li>• Contractual requirements</li> </ul> |
| S9.8.4          | EC15                    | Strict enforcement on no-dumping  | Minimise the potential impact to marine habitats                                      | Contractor                  | In reclamation area as well as all works area and travel route of works vessels | Before and during construction phase | <ul style="list-style-type: none"> <li>• EIA</li> <li>• Contractual requirements</li> </ul> |
| S9.8.4          | EC16                    | Spill response plan   | Minimise the potential impact to marine habitats                                      | Contractor                  | In reclamation area as well as all works area and travel route of works vessels | Before and during construction phase | <ul style="list-style-type: none"> <li>• EIA</li> <li>• Contractual requirements</li> </ul> |
| S.9.8.4         | EC17                    | Control and minimization of marine traffic by including using larger-sized barges, land transportation of materials, reuse of excavation and C&D materials and speed limits & | Reduce marine traffic   | Contractor                  | In reclamation area as well   | Construction phase                   | <ul style="list-style-type: none"> <li>• EIA</li> <li>• Contractual</li> </ul>              |

**Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension**

| <b>EIA Ref.</b> | <b>EM&amp;A Log Ref</b> | <b>Recommended Mitigation Measures</b>   | <b>Objectives of the Recommended Measures &amp; Main Concerns to address</b> | <b>Implementation Agent</b>   | <b>Location / Timing</b>                            | <b>Implementation Stage</b>   | <b>Requirements and / or standards to be achieved</b>  |
|-----------------|-------------------------|--|--|---|---|---|--|
|                 |                         | regular routes of works vessels  |  |   | as all works area and travel route of works vessels |   | requirements   |
| S9.8.4          | EC18                    | Dolphin exclusion zone and dolphin watching plan   | Protection of CWD  | Contractor  | In reclamation area as well as all works area       | Construction phase  | <ul style="list-style-type: none"> <li>• EIA</li> <li>• Contractual requirements</li> </ul>  |
| S9.8.4          | EC19                    | Speed limits and regular routes of works vessels;<br>Prepare and submit a “Works Vessel Travel Route Plan” | Protection of CWD  | Contractor  | In reclamation area as well as all works area       | Construction phase  | <ul style="list-style-type: none"> <li>• EIA</li> <li>• Contractual requirements</li> </ul>  |
| S9.11.1         | EC20                    | Monitoring of compensatory planting woodland   | Monitor the survival of trees and establishment of the woodland              | CEDD/<br>Contractor   | Areas of compensatory woodland planting             | Quarterly for 3 years after completion of planting works  | <ul style="list-style-type: none"> <li>• EIA</li> <li>• Contractual requirements</li> </ul>  |
| S9.11.1         | EC21                    | Monitoring of translocated amphibians  | Monitor the effectiveness of the translocation programme                     | Public works:<br>Responsible government departments / Contractor<br><br>Private lots:<br>Private developers | Release sites for translocated amphibians           | After translocation exercise.<br><br>At least three surveys in each release site during the breeding season, preferably monthly between April and June, | <ul style="list-style-type: none"> <li>• EIA</li> <li>• Contractual requirements</li> <li>• Explanatory statement of the OZP (for private lots)</li> </ul> |
| S9.11.1         | EC22                    | Monitoring of preserved / transplanted plant species   | Monitor and evaluate   | Public works:   | Construction  | After   | <ul style="list-style-type: none"> <li>• EIA</li> </ul>  |

**Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension**

| <b>EIA Ref.</b>                           | <b>EM&amp;A Log Ref</b> | <b>Recommended Mitigation Measures</b>                         | <b>Objectives of the Recommended Measures &amp; Main Concerns to address</b> | <b>Implementation Agent</b>   | <b>Location / Timing</b>  | <b>Implementation Stage</b>   | <b>Requirements and / or standards to be achieved</b>   |
|---|-------------------------|--|--|---|---|---|---|
|   |                         |  | the effectiveness of the preservation and transplantation programme.         | Responsible government departments / Contractor<br><br>Private lots: Private developers | sites for preserved plants; recipient sites for transplanted plants | transplantation or preservation.<br><br>For transplanted individuals, for two years, monthly for the first year, and then quarterly for the second year.<br><br>For the preserved individuals, monthly throughout the construction. | <ul style="list-style-type: none"> <li>• Contractual requirements</li> <li>• Explanatory statement of the OZP (for private lots)</li> </ul> |
| S9.11.1                                   | EC23                    | Monitoring of Tung Chung Stream and Wong Lung Hang Stream EISs | Protect the EISs   | Contractor  | Tung Chung Stream and Wong Lung Hang Stream                         | Construction phase and post-construction phase  | <ul style="list-style-type: none"> <li>• EIA</li> <li>• Contractual requirements</li> </ul>   |
| 9.11.2                                    | EC24                    | Monitoring of Tung Chung Bay and Tai Ho Wan                    | Protect Tung Chung Bay and Tai Ho Wan  | Contractor  | Tung Chung Bay and Tai Ho Wan                                       | Construction phase and post-construction phase  | <ul style="list-style-type: none"> <li>• EIA</li> <li>• Contractual requirements</li> </ul>   |
| <b><i>Ecology (Operational Phase)</i></b> |                         |  |  |   |   |   |   |
| S9.11.1                                   | EC25                    | Monitoring of emergent plant inside River Park                 | Monitor the survival of emergent plant                                       | DSD/ Contractor   | Three months after completion of planting in future River Park      | Quarterly for 2 years after completion of planting works  | <ul style="list-style-type: none"> <li>• EIA</li> <li>• Contractual requirements</li> </ul>   |

**Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension**

| <b>EIA Ref.</b> | <b>EM&amp;A Log Ref</b> | <b>Recommended Mitigation Measures</b> | <b>Objectives of the Recommended Measures &amp; Main Concerns to address</b>   | <b>Implementation Agent</b> | <b>Location / Timing</b>             | <b>Implementation Stage</b>   | <b>Requirements and / or standards to be achieved</b>                                       |
|-----------------|-------------------------|--|--|-----------------------------|--------------------------------------|---|---|
| 9.11.2          | EC26                    | Eco-shoreline monitoring               | Monitor the colonisation and establishment of fauna and/or flora, water quality, and recruitments of fisheries species | CEDD/<br>Contractor         | Eco-shoreline at TCE PDA reclamation | Post-construction phase, twice in wet and dry seasons respectively, at least 3 years, subject to review | <ul style="list-style-type: none"> <li>• EIA</li> <li>• Contractual requirements</li> </ul> |

**Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension**

| <b>EIA Ref.</b>  | <b>EM&amp;A Log Ref</b> | <b>Recommended Mitigation Measures</b>  | <b>Objectives of the Recommended Measures &amp; Main Concerns to address</b> | <b>Implementation Agent</b> | <b>Location</b>           | <b>Implementation Stage</b>            | <b>Requirements and / or standards to be achieved</b>                                       |
|------------------|-------------------------|---|--|-----------------------------|---------------------------|--|---|
| <i>Fisheries</i> |                         |   |  |                             |                           |  |   |
| S10.8            | F1                      | Good Site Practices   | To protect the fisheries resources   | Contractor                  | In reclamation area       | Construction phase                     | <ul style="list-style-type: none"> <li>• EIA</li> <li>• Contractual requirements</li> </ul> |
| S10.8            | F2                      | No dumping  | To protect the fisheries resources   | Contractor                  | In reclamation area       | Construction phase                     | <ul style="list-style-type: none"> <li>• EIA</li> <li>• Contractual requirements</li> </ul> |
| S10.8            | F3                      | Spill response plan   | To protect the fisheries resources   | Contractor                  | In reclamation area       | Construction phase                     | <ul style="list-style-type: none"> <li>• EIA</li> <li>• Contractual requirements</li> </ul> |
| S10.9            | F4                      | Follow the mitigation measures proposed in the water quality assessment for the construction and operation phases of the project. | To protect the fisheries resources   | Contractor                  | Waters in Northern Lantau | Construction phase and operation phase | <ul style="list-style-type: none"> <li>• EIA</li> <li>• Contractual requirements</li> </ul> |
| S10.9            | F5                      | Follow the mitigation measure of eco-shoreline in ecology chapter for the construction and operation phases of the project.       | To enhance the fisheries resources   | Contractor                  | Eco-shorelines            | Construction phase and operation phase | <ul style="list-style-type: none"> <li>• EIA</li> <li>• Contractual requirements</li> </ul> |

**Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension**

| <b>EIA Ref.</b>                                  | <b>EM&amp;A Log Ref</b> | <b>Recommended Mitigation Measures</b>   | <b>Objectives of the Recommended Measures &amp; Main Concerns to address</b>       | <b>Implementati on Agent</b>                     | <b>Location</b>   | <b>Implementation Stage</b>                | <b>Requirements and / or standards to be achieved</b>   |
|--|-------------------------|--|--|--|---|--|---|
| <i>Landscape and Visual (Construction Phase)</i> |                         |  |  |  |   |  |   |
| S11.7<br>MM1                                     | LV1                     | <p>Optimisation of Construction Areas &amp; Providing Temporary Landscape on Temporary Construction – Construction areas’ control shall be enforced, where possible, to ensure that the landscape and visual impacts arising from the construction activities are minimised.</p> <p>It includes reduction of the extent of working areas and temporary works areas, management on storing and using the construction equipment and materials, and consideration of detailed schedules to shorten the construction period. Temporary landscape treatments are considered to be adopted such as applying hydro-seeding on temporary stockpiles and reclamation areas to alleviate the potential impacts.</p> | Minimise the landscape and visual impacts arising from the construction activities | Relevant Government Departments / Private Sector | Through-out Tung Chung West (TCW) area and Tung Chung East (TCE) area | Construction Phase                         |   |
| S11.7<br>MM2                                     | LV2                     | <p>Minimize Topographical Change – The footprint of construction elements and temporary works areas should be optimised to reduce topographical/ landform changes, as well as reduce land take and interference with natural terrain. Where there is a need to significantly cut into the existing landform, retaining walls and cut slopes should be considered as appropriate.</p> <p>To minimize landform changes and land resumption, earthworks and engineered slopes should be designed to be a visually interesting, compatible with the surrounding landscape and to mimic the natural contouring and terrain as appropriate.</p>  | Reduce topographical changes and minimize land resumption                          | Relevant Government Departments / Private Sector | Through-out TCW area  | Prior to Construction & Construction Phase | <ul style="list-style-type: none"> <li>• GEO Publication No/1/2011, Technical Guidelines on Landscape Treatment for Slopes</li> </ul> |
| S11.7<br>MM3                                     | LV3                     | Preservation of Potentially Registerable OVTs, Rare and Protective Vegetation – Existing trees to be retained within the Project Site should be carefully protected during construction. In particular Potentially Registerable OVTs are considered to be preserved according to ETWB  | Protect and Preserve Trees   | Relevant Government Departments / Private Sector | Onsite, particularly for TCW area                                     | Prior to Construction & Construction Phase | <ul style="list-style-type: none"> <li>• ETWB TC(W) No.29/2004 and DEVB TC(W)</li> </ul>  |



**Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension**

| EIA Ref.     | EM&A Log Ref | Recommended Mitigation Measures   | Objectives of the Recommended Measures & Main Concerns to address | Implementation Agent                             | Location  | Implementation Stage                       | Requirements and / or standards to be achieved  |
|--------------|--------------|---|---|--|---|--|---|
|              |              | <p>Technical Circular (Works) No. 29/2004. Rare and Protective Vegetation shall be protected following Forestry Regulations (Cap.96) and Protection of Endangered Species of Animals and Plants Ordinance (Cap.586). Detailed Tree Protection Specification shall be provided in the Contract Specification according to DEVB TCW No. 10/2013 Tree Preservation. Following DEVB (GLTM) Guidelines for Tree Preservation during Development, the Contractor shall be required to submit, for approval, a detailed working method statement for the protection of trees prior to undertaking any works adjacent to all retained trees, including trees in contractor's works areas.</p> <p>A detailed tree survey will be carried out for the Tree Removal Application (TRA) process which will be carried out at the later detailed design stage of the Project. The detailed tree survey will propose which trees should be retained, transplanted or felled and will include details of tree protection measures for those trees to be retained.</p> |   |  |   |  | <p>No.10/2013.</p> <ul style="list-style-type: none"> <li>• Greening, Landscape and Tree Management Section (GLTM) of the Development Bureau, Guidelines on Tree Preservation during Development (April, 2015)</li> </ul> |
| S11.7<br>MM4 | LV4          | <p>Transplanting of Existing Trees – Trees unavoidably affected by the Project works should be transplanted where practical. Trees should be transplanted straight to their final receptor locations within the site and not held in a temporary nursery as far as possible.</p> <p>A detailed Tree Transplanting Specification shall be provided in the Contract Specification, where applicable. Sufficient time for necessary tree root and crown preparation periods shall be allowed in the project programme. A detailed transplanting proposal will be submitted to relevant government departments for approval in accordance with DEVB TCW 10/2013 and LAO PN 7/2007 and final locations of transplanted trees should be agreed prior to commencement of the work.</p> <p>For trees associated with highways e.g. roadside planting</p>  | Transplant Trees where suitable for transplantation               | Relevant Government Departments / Private Sector | Onsite where possible, otherwise consider offsite locations | Prior to Construction & Construction Phase | <ul style="list-style-type: none"> <li>• DEVB TC(W) No.10/2013 and LAO PN7/2007</li> <li>• HyD HQ/GN/13 Interim Guidelines for Tree Transplanting Works under Highways Department's Vegetation Maintenance</li> </ul>     |

**Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension**

| <b>EIA Ref.</b> | <b>EM&amp;A Log Ref</b> | <b>Recommended Mitigation Measures</b>  | <b>Objectives of the Recommended Measures &amp; Main Concerns to address</b>                            | <b>Implementation Agent</b>                      | <b>Location</b>               | <b>Implementation Stage</b>                | <b>Requirements and / or standards to be achieved</b>   |
|-----------------|-------------------------|---|---|--|-------------------------------|--|---|
|                 |                         | along highways, that are unavoidably affected and should be transplanted. HyD HQ/GN/13 'Interim Guidelines for Tree Transplanting Works under Highways Department's Vegetation Maintenance Ambit' should be referred to.  |   |  |                               |  | <ul style="list-style-type: none"> <li>Ambit</li> <li>GLTM of the Development Bureau, Guidelines on Tree Preservation during Development (April, 2015)</li> </ul> |
| S11.7 MM5       | LV5                     | <p>Screen hoarding – To reduce negative visual impact, construction site hoarding should be erected around the site to screen pedestrian level views into the construction area from visual sensitive receivers.</p> <p>Hoarding design should consider greening measures such as colour and form should be adopted to improve its visual appearance.</p>   | To screen undesirable views of the work site.   | Relevant Government Departments / Private Sector | Through-out TCW and TCE areas | Construction Phase                         |   |
| S11.7 MM6       | LV6                     | Adopting Non-dredge Method for the Reclamation – In order to minimize the potential adverse impacts caused by the reclamation, a number of alternative construction methodologies has been critically examined. After considering all the options such as fully dredged, partially dredged and non-dredged methods for seawall construction and reclamation, non-dredged method for both the seawall construction and reclamation are recommended so as to minimize the generation of dredged sediment. | Minimize the potential adverse impacts caused by the reclamation  | Relevant Government Departments / Private Sector | Through-out TCE area          | Construction Phase                         | <ul style="list-style-type: none"> <li>Foreshore and Sea-bed (Reclamations) Ordinance (Cap.127)</li> </ul>  |
| S11.7 MM7       | LV7                     | Protection of Natural Rivers and Streams – For all the natural rivers and streams inside the development area, in accordance with ETWB TCW 5/2005, consideration of protection measures should be made to minimize any impacts from the construction works, especially those  | <p>Protection of Natural Rivers and Streams</p> <p>Minimize the impacts from the construction works</p> | Relevant Government Departments / Private Sector | Through-out TCW area          | Prior to Construction & Construction Phase | <ul style="list-style-type: none"> <li>EPD ProPECC PN1/94 Construction Site Drainage.</li> <li>DSD Technical</li> </ul>   |

**Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension**

| <b>EIA Ref.</b> | <b>EM&amp;A Log Ref</b> | <b>Recommended Mitigation Measures</b>   | <b>Objectives of the Recommended Measures &amp; Main Concerns to address</b> | <b>Implementation Agent</b>            | <b>Location</b>              | <b>Implementation Stage</b>                           | <b>Requirements and / or standards to be achieved</b>   |
|-----------------|-------------------------|--|--|--|------------------------------|---|---|
|                 |                         | <p>development near Tung Chung Stream.</p> <p>According to the latest RODP, a 30m buffer zone will be zoned as “CA”. Precast structures or other similar approaches will be used to prevent / minimise any construction works in river and thus to avoid any direct water quality impact. Good site management as stipulated in ProPECC PN1/94 will be fully implemented to avoid polluted liquid or solid wastes from falling into the river waters.</p>  |  |  |                              |   | <p>Circular No. 2/2004.</p> <ul style="list-style-type: none"> <li>• ETWB TC(W) No.5/2005 Protection of natural streams/ rivers from adverse impacts arising from construction works</li> </ul> |
| S11.7 MM8       | LV8                     | <p>Preservation of Natural Coastline – The natural coastline along the proposed “RO” of the RODP in TCW should be preserved. The remaining natural shorelines in Tung Chung Bay including sandy shores close to the Tung Chung old pier will be conserved as a Waterfront Park according to the latest RODP.</p>   | <p>Preservation of Natural Coastline</p>                                     | <p>Relevant Government Departments</p> | <p>Onsite where possible</p> | <p>Prior to Construction &amp; Construction Phase</p> |   |
| S11.7 MM9       | LV9                     | <p>Providing Natural Rock Material/ Planting for Artificial Seawall – There would be inevitable permanent losses of marine waters (seabed and water column), and direct impacts on existing artificial seawalls due to the reclamation. To minimize the impacts, the design of the future seawall like ‘eco-shoreline’ could be improved to provide high ecological functions and mitigate the impact of the loss.</p> <p>An ‘eco-shoreline’ is any shoreline which provides beneficial functions to the local ecosystem through a range of active or passive solutions, whilst providing coastal protection. By means of using natural rock materials for artificial seawall and considering to introduce a native vegetation buffer directly behind the top of seawalls as appropriate to create habitat, shelter and a source of food</p> | <p>Mitigate the impacts on existing artificial seawalls</p>                  | <p>Relevant Government Departments</p> | <p>Onsite where possible</p> | <p>Prior to Construction &amp; Construction Phase</p> |   |

**Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension**

| <b>EIA Ref.</b>  | <b>EM&amp;A Log Ref</b> | <b>Recommended Mitigation Measures</b>  | <b>Objectives of the Recommended Measures &amp; Main Concerns to address</b>       | <b>Implementation Agent</b>                      | <b>Location</b>                                   | <b>Implementation Stage</b>  | <b>Requirements and / or standards to be achieved</b>  |
|--|-------------------------|---|--|--|---|--|--|
|  |                         | for benefiting both terrestrial and aquatic species along the foreshore, these measures can help to enhance the ecological functions and ‘natural-look’ of the shoreline, and the potential impacts will be mitigated.  |  |  |   |  |  |
| <b><i>Landscape and Visual (Operational Phase)</i></b> |                         |   |  |  |   |  |  |
| S11.7<br>MM10  | LV10                    | <p>Compensatory Planting – Compensatory planting for felled trees shall be provided to the satisfaction of relevant Government departments. Required numbers and locations of compensatory trees shall be determined and agreed separately with Government during the Tree Removal Application process under DEVB TCW No. 10/2013 and LAO PN 7/2007.</p> <p>The location of compensatory planting is proposed at the potential open areas such as open spaces, amenity areas, open areas of the streetscapes including roadside planting, as well as the open areas within development lots.</p> <p>The species to be planted should be all native species, taken “Characteristics of Major Local Tree Species Propagated by AFCD” as a reference. A search of species to be planted will be conducted in a further detailed stage.</p> | Compensate for trees and shrubs lost due to the Project                            | Relevant Government Departments / Private Sector | Onsite where possible, particular-ly for TCW area | Prior to Construction, Construction Phase & Maintenance in Operation Phase | <ul style="list-style-type: none"> <li>• DEVB TC(W) No.10/2013 and LAO PN 7/2007.</li> <li>• GLTM of the Development Bureau, Guidelines on Tree Preservation during Development (April, 2015)</li> </ul> |
| S11.7<br>MM11  | LV11                    | Woodland Restoration – A search of area to mitigate the loss of woodland has been conducted. Priority has been given to the practicability of compensation of woodland within the boundary of RODP. Given the nature of the project is to provide development opportunities to satisfy the needs for the society in general and the aspirations of local communities, compensation of woodland is only possible for the areas beyond the RODP. It is considered that the areas adjoining the woodlands near the existing services reservoirs, and hillsides to the east of Tung Chung Road, would be suitable locations. The advantage of these locations is that there are existing woodlands immediately  | Reprovide areas of woodland to compensate for those areas of quality woodland lost | CEDD /AFCD                                       | In areas identified and as agreed with AFCD       | Prior to Construction, Construction Phase & Maintenance in Operation Phase | <ul style="list-style-type: none"> <li>• DEVB Technical Circular Works 10/2013- Tree Preservation</li> <li>• GLTM of the Development Bureau, Guidelines on Tree Preservation</li> </ul>                  |

**Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension**

| <b>EIA Ref.</b> | <b>EM&amp;A Log Ref</b> | <b>Recommended Mitigation Measures</b>   | <b>Objectives of the Recommended Measures &amp; Main Concerns to address</b>                                   | <b>Implementati on Agent</b>    | <b>Location</b>  | <b>Implementation Stage</b>  | <b>Requirements and / or standards to be achieved</b>  |
|-----------------|-------------------------|--|--|---------------------------------|--|--|--|
|                 |                         | <p>downhill to the location and the Sheung Ling Pei Fung Shui Wood is further downhill behind Sheung Ling Pei Village, planting new woodland areas adjoining existing woodlands would form an ecological linkage and increase the overall habitat size, and hence would help to enhance the ecological and landscape values in the long run.</p> <p>It is noted that the compensation trees for landscape impacts will also be planted near the future service reservoirs. The tree species to be planted should be all native species for woodland compensation, and the two areas uphill to Sheung Ling Pei should also make reference to the existing tree species reported in Fung Shui Woods habitat.</p> |  |                                 |  |  | during Development (April, 2015)   |
| S11.7<br>MM12   | LV12                    | Screen Planting – Tall screen/buffer trees and shrubs should be planted to screen proposed structures such as roads and buildings. This measure will form part of the compensatory planting and will improve compatibility with the surrounding environment and create a pleasant pedestrian environment.  | <p>To screen proposed structures</p> <p>Improve compatibility with the surrounding environment</p>             | Relevant Government Departments | Through-out the working sites of the TCW and TCE areas | Prior to Construction, Construction Phase & Maintenance in Operation Phase | <ul style="list-style-type: none"> <li>HyD HQ/GN/15– Guidelines for Greening Works along Highways.</li> </ul>  |
| S11.7<br>MM13   | LV13                    | Roadside Planting – Roadside greening is proposed alongside all roads within the possible developments. It will enhance local identity, if theme planting is used, and reduce visual impact through screening. At-grade road planting should be considered along central dividers and on road islands e.g. in the middle of roundabouts.   | <p>Soften the hard, straight edges and provide greening along the roads;</p> <p>Improve the visual amenity</p> | Relevant Government Departments | Along new roads, and On appropriate viaducts           | Prior to Construction, Construction Phase & Maintenance in Operation Phase | <ul style="list-style-type: none"> <li>HyD HQ/GN/15– Guidelines for Greening Works along Highways.</li> <li>Development Bureau Technical Circular Works No.2/2012 – Allocation of Space for Quality</li> </ul> |

**Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension**

| EIA Ref. | EM&A Log Ref | Recommended Mitigation Measures | Objectives of the Recommended Measures & Main Concerns to address | Implementation Agent | Location | Implementation Stage | Requirements and / or standards to be achieved |
|----------|--------------|---------------------------------|---|----------------------|----------|----------------------|--|
|          |              |                                 |   |                      |          |                      | Greening on Roads                              |

**Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension**

| <b>EIA Ref.</b> | <b>EM&amp;A Log Ref</b> | <b>Recommended Mitigation Measures</b>  | <b>Objectives of the Recommended Measures &amp; Main Concerns to address</b>  | <b>Implementation Agent</b>     | <b>Location</b>                         | <b>Implementation Stage</b>  | <b>Requirements and / or standards to be achieved</b>   |
|-----------------|-------------------------|---|---|---------------------------------|---|--|---|
| S11.7<br>MM14   | LV14                    | Aesthetic Design of Built Development – The planning of the revised RODP has considered reducing potential visual impacts, enhancing visual amenity and keeping visual corridors. The proposed development will ensure the building massing is compatible with its surroundings. To improve visual amenity, natural building materials could be used on building facades. For example, stone and timber should be considered for architectural features; light earthy tone colours such as shades of green, shades of grey, shades of brown and off-white should be considered for the façade treatment to reduce the visibility of the development components. The form, textures, finishes and colours of the proposed development components should aim to be compatible with the existing surroundings. It would only be implemented for public developments/projects.  | Improve visual amenity of the new buildings, keep visual corridors and integrate as possible into the surrounding landscape                       | Relevant Government Departments | Through-out the TCW and TCE areas       | Prior to Construction, Maintenance in Operation Phase                      | <ul style="list-style-type: none"> <li>• Hong Kong Planning Standards and Guidelines (HKPSG) issued by the Planning Department (As at Aug 2011);</li> <li>• PNAP APP-152, Sustainable Building Design Guidelines</li> </ul>             |
| S11.7<br>MM15   | LV15                    | Maximise Greening on Structures – The Government has been actively promoting greening in buildings and structures such as bridges to improve the environment. This includes actively implementing rooftop greening or vertical greening, as where practicable to enhance the cityscape and mitigate the heat island effect in urban areas. For the new built forms in TCW and TCE, it is considered the implementation of the following greening measures could alleviate the landscape and visual impacts of new development and help the development blend in with its surrounding landscape: <ul style="list-style-type: none"> <li>• Sky Garden: Refuge floors or voids in building mass formed by partial removal of floor plates on certain building storeys or provision of freed up areas on certain building storeys provide opportunities for sky gardens for the proposed built development. It can allow views through the development to the background formed by the natural hillsides and</li> </ul> | <p>Maximise Greening coverage</p> <p>Enhance visual amenity, create visual corridors and integrate as possible into the surrounding landscape</p> | Relevant Government Departments | On appropriate buildings and structures | Prior to Construction, Construction Phase & Maintenance in Operation Phase | <ul style="list-style-type: none"> <li>• Development Bureau Technical Circular (Works) No. 3/2012 Site Coverage of Greenery for Government Building Projects</li> <li>• PNAP APP-152, Sustainable Building Design Guidelines</li> </ul> |

**Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension**

| EIA Ref. | EM&A Log Ref | Recommended Mitigation Measures  | Objectives of the Recommended Measures & Main Concerns to address | Implementati on Agent | Location | Implementation Stage | Requirements and / or standards to be achieved |
|----------|--------------|--|---|-----------------------|----------|----------------------|--|
|          |              | <p>enhance the visual amenity effectively. For public developments, relevant technical document Technical Circular (Works) No. 3/2012 Site Coverage of Greenery for Government Building Projects by Development Bureau in 2011 shall be referred to. For private developments, it is only applicable to sites with inadequate greening coverage and should be implemented in accordance with Sustainable Building Design Guidelines PNAP APP-152.</p> <ul style="list-style-type: none"> <li>• Green Roof: The Architectural Services Department completed the Study on Green Roof Application in Hong Kong in 2007 which reviewed the latest concepts and design technology of green roof and recommended technical guidelines suitable for application in Hong Kong. The study will be taken into account to the new buildings to be built in TCW and TCE. Landscape and visual impact can be alleviated and the landscape and visual value can be enhanced. For private development, it is only applicable to sites with inadequate greening coverage and should be implemented in accordance with Sustainable Building Design Guidelines PNAP APP-152. Relevant technical document Technical Circular (Works) No. 3/2012 Site Coverage of Greenery for Government Building Projects by Development Bureau in 2011 shall be reference. For public developments, relevant technical document Technical Circular (Works) No. 3/2012 Site Coverage of Greenery for Government Building Projects by Development Bureau in 2011 shall be referred to. For private developments, it is only applicable to sites with inadequate greening coverage and should be implemented in accordance with Sustainable Building Design Guidelines PNAP APP-152.</li> <li>• Vertical Green: Planting of climbers to grow up</li> </ul> |   |                       |          |                      |  |



**Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension**

| EIA Ref.      | EM&A Log Ref | Recommended Mitigation Measures   | Objectives of the Recommended Measures & Main Concerns to address       | Implementation Agent | Location   | Implementation Stage  | Requirements and / or standards to be achieved   |
|---------------|--------------|---|---|----------------------|--|---|--|
|               |              | <p>vertical surfaces where appropriate (e.g. building edges), to soften hard structures and facilities. Relevant technical document Technical Circular (Works) No. 3/2012 Site Coverage of Greenery for Government Building Projects by Development Bureau in 2011 shall be observed. For public developments, relevant technical document Technical Circular (Works) No. 3/2012 Site Coverage of Greenery for Government Building Projects by Development Bureau in 2011 shall be reference. For private development, it is only applicable to sites with inadequate greening coverage and should be implemented in accordance with Sustainable Building Design Guidelines PNAP APP-152.</p> <ul style="list-style-type: none"> <li>Greening on infrastructure: Planting could be provided on infrastructure such as bridges where appropriate to enhance greenery to soften its built edges. Screen planting could be provided near infrastructure to reduce any undesirable visual impacts.</li> </ul> |   |                      |  |   |  |
| S11.7<br>MM16 | LV16         | <p>Noise barrier design – The visual impact of noise mitigation measures will be mitigated by appropriate detailed design, including suitable combination of transparent and sound absorbent materials, appropriate colour selection of panels and supporting structures, or provision of at-grade planting of trees, shrubs and/or climbers camouflage to the barriers, as well as design of supporting structures to incorporate a high level of quality and aesthetics. A combination of transparent panels at top and solid panels at bottom would lighten the visual impact, and at the same time maintain the attractiveness by using colourful panels. The noise barriers would be implemented for District Distributor Roads and Local Distributor Roads at both TCE and TCW area.</p>  | <p>Minimize the visual impact from the structures of noise barriers</p> | HyD                  | <p>Noise barriers within the TCW and TCE areas</p> | <p>Prior to Construction, Construction Phase &amp; Maintenance in Operation Phase</p> | <ul style="list-style-type: none"> <li>GLTM of the Development Bureau’s Guidelines on Greening of Noise Barriers (April 2012).</li> <li>Guidelines on Design of Noise Barriers by HyD and EPD in 2003</li> </ul> |

**Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension**

| <b>EIA Ref.</b>   | <b>EM&amp;A Log Ref</b> | <b>Recommended Mitigation Measures</b>  | <b>Objectives of the Recommended Measures &amp; Main Concerns to address</b>     | <b>Implementati on Agent</b> | <b>Location</b>                                      | <b>Implementation Stage</b>  | <b>Requirements and / or standards to be achieved</b>  |
|---|-------------------------|---|--|------------------------------|--|--|--|
| S11.7<br>MM17   | LV17                    | <p>Landscape Treatment for Polders &amp; Attenuation Ponds – There would be polders and attenuation ponds in TCW. While they are primarily used for receiving and treating surface runoff and alleviating the flood risk during heavy rainfall, the design of those has provided an opportunity to have a synergy to enhance both the ecological and landscape values together.</p> <p>Depending on detailed design, part of these attenuation ponds (mainly the biofiltration zone) could be refined in an appropriate manner, without compromising its primary functions of treating surface runoff and flood protection, to incorporate ecological and landscape design such as planting of aquatic plants and butterfly foodplant for providing the landscape and ecological enhancement.</p> | Enhance the landscape and visual value   | DSD                          | Polders & Attenuation Ponds where possible           | Prior to Construction, Construction Phase & Maintenance in Operation Phase |  |
| <b><i>Landscape and Visual (Construction &amp; Operational Phase)</i></b> |                         |   |  |                              |  |  |  |
| S11.7<br>MM18   | LV18                    | <p>Landscaping on Slopes – Hydro seeding of modified slopes should be done as soon as grading works are completed to prevent erosion and subsequent loss of landscape resources and character. Woodland tree seedlings and/ or shrubs should be planted where gradient and site conditions allow.</p> <p>In addition, landscape planting should be provided for the retaining structures associated with modified slopes where condition allow.</p>   | Enhance landscape value, plant diversity and their visual appearance             | CEDD                         | Onsite, particularly in TCW area                     | Prior to Construction, Construction Phase & Maintenance in Operation Phase | <ul style="list-style-type: none"> <li>• GEO Publication No.1/2011 Technical Guidelines on Landscape Treatment for Slopes by CEDD in 2011</li> </ul> |
| S11.7<br>MM19   | LV19                    | Landscape Treatment on Channelized Watercourses – For the channelized watercourses in Tung Chung Stream that will be dechannelized, the Drainage Services Department Practice Note No.1/2005 – Guidelines on Environmental Considerations for River Channel Design, should be considered and appropriate measures included ensuring the new watercourses match the existing as far as possible.   | <p>Avoid direct impacts on the watercourse</p> <p>Improve the visual amenity</p> | CEDD                         | The channelized watercourses throughout the TCW area | Prior to Construction, Construction Phase & Maintenance in Operation Phase | <ul style="list-style-type: none"> <li>• Drainage Services Department Practice Note No.1/2005 – Guidelines on Environmental</li> </ul>               |

**Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension**

| <b>EIA Ref.</b> | <b>EM&amp;A Log Ref</b> | <b>Recommended Mitigation Measures</b>   | <b>Objectives of the Recommended Measures &amp; Main Concerns to address</b> | <b>Implementation Agent</b>                      | <b>Location</b>                   | <b>Implementation Stage</b>          | <b>Requirements and / or standards to be achieved</b> |
|-----------------|-------------------------|--|--|--|-----------------------------------|--------------------------------------|---|
|                 |                         | Measures can include enhancement planting to upgrade the channels as appropriate, including consideration of wetland planting along embankments where appropriate; as well as consideration of the best materials for the channel lining (e.g. gabion).                              |  |  |                                   |                                      | Considerations for River Channel Design               |
| S11.7<br>MM20   | LV20                    | Light Control – Construction day and night time lighting should be controlled to minimize glare impact to adjacent VSRs during the construction stage. Street and night time lighting shall also be controlled to minimize glare impact to adjacent VSRs during the operation phase. | Minimize negative glare impact to adjacent VSRs                              | Relevant Government Departments / Private Sector | Through-out the TCW and TCE areas | Construction Phase & Operation Phase |   |

**Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension**

| <b>EIA Ref.</b>  | <b>EM&amp;A Log Ref</b> | <b>Recommended Mitigation Measures</b>  | <b>Objectives of the Recommended Measures &amp; Main Concerns to address</b>  | <b>Implementation Agent</b>           | <b>Location / Timing</b>                                  | <b>Implementation Stage</b>                               | <b>Requirements and / or standards to be achieved</b>  |
|--|-------------------------|---|---|---------------------------------------|---|---|--|
| <i>Cultural Heritage Impact (Construction and Operational Phase)</i> |                         |   |   |                                       |   |   |  |
| S.12.5   | CH1                     | <u>Terrestrial Archaeology</u> <ul style="list-style-type: none"> <li>Implement rescue excavations/ survey-cum-rescue excavations/ further surveys after land resumption and prior to any construction works (see <b>Figure 14.1</b> for the locations of rescue excavations/survey-cum-rescue excavations/further survey)</li> </ul> | 1) Rescue excavations to salvage archaeological data and cultural materials<br>2) Survey-cum-rescue excavations to better locate and design the follow up rescue excavations<br>3) Further surveys to obtain sufficient data for formulation of appropriate mitigation measures | Contractor / Future Private Developer | After land resumption and prior to any construction works | After land resumption and prior to any construction works | <ul style="list-style-type: none"> <li>Guidelines for Cultural Heritage Impact Assessment</li> <li>TM-EIAO Annex 10 and Annex 19</li> <li>Antiquities and Monuments Ordinance</li> </ul> |
| S.12.5   | CH2                     | <u>Terrestrial Archaeology</u> <ul style="list-style-type: none"> <li>Implement watching brief during construction phase (see <b>Figure 14.1</b> for the locations of watching brief)</li> </ul>  | To identify and record any archaeological material or features revealed during construction phase   | Contractor / Future Private Developer | During construction phase                                 | During construction phase                                 |  |

**Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension**

| <b>EIA Ref.</b>         | <b>EM&amp;A Log Ref</b> | <b>Recommended Mitigation Measures</b>   | <b>Objectives of the Recommended Measures &amp; Main Concerns to address</b> | <b>Implementation Agent</b> | <b>Location / Timing</b> | <b>Implementation Stage</b> | <b>Requirements and / or standards to be achieved</b>   |
|-------------------------|-------------------------|--|--|-----------------------------|--------------------------|-----------------------------|---|
| <i>EM&amp;A Project</i> |                         |  |  |                             |                          |                             |   |
| S13.2                   | EM1                     | An Independent Environmental Checker needs to be employed as per the EM&A Manual.  | Control EM&A Performance   | Project Proponent           | All construction sites   | Construction stage          | <ul style="list-style-type: none"> <li>• EIAO Guidance Note No.4/2010</li> <li>• TM-EIAO</li> </ul> |
| S13.2 – 13.4            | EM2                     | 1) An Environmental Team needs to be employed as per the EM&A Manual.<br>2) Prepare a systematic Environmental Management Plan to ensure effective implementation of the mitigation measures.<br>3) An environmental impact monitoring needs to be implementing by the Environmental Team to ensure all the requirements given in the EM&A Manual are fully complied with. | Perform environmental monitoring & auditing                                  | Project Proponent           | All construction sites   | Construction stage          | <ul style="list-style-type: none"> <li>• EIAO Guidance Note No.4/2010</li> <li>• TM-EIAO</li> </ul> |

**Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension**

| Docum ent Ref.   | EM&A Log Ref | Recommended Mitigation Measures   | Objectives of the Recommended Measures & Main Concerns to address | Implementation Agent | Location / Timing              | Implementation Stage | Requirements and / or standards to be achieved  |
|--|--------------|---|---|----------------------|--------------------------------|----------------------|---|
| <i>Works Vessel Travel Routes (Extracted from Works Vessel Travel Route Plan submitted under Condition 2.13 of the EP)</i> |              |   |   |                      |                                |                      |   |
| S3.2   | WVTR1        | All works vessels shall be equipped with Global Positional System (GPS) or equivalent automatic identification system (AIS) for real time tracking and monitoring of their travel routing, speed and anchorage points. The system shall be capable to record and analyse the travel routing, speed and anchorage points.  | Control EM&A Performance  | Contractor           | All marine constructi on sites | Construction stage   | <ul style="list-style-type: none"> <li>• EIA</li> <li>• Contractual requirements</li> </ul> |
| S3.3.1   | WVTR2        | <p>1) Once approaching or leaving the entrance of the silt curtain, all vessels will travel at a speed no greater than 8 knots between the site and boundary of The Brothers Marine Park. The vessels can then navigate at normal speed (8-12 knots) after that distance unless other restrictions are imposed.</p> <p>2) If any dolphins are sighted within 250m of a vessel then the vessel will slow down to a speed no greater than 5 knots for at least 3 minutes after the last sighting.</p> | Protection of CWD   | Contractor           | All marine constructi on sites | Construction stage   | <ul style="list-style-type: none"> <li>• EIA</li> <li>• Contractual requirements</li> </ul> |
| S3.3.2   | WVTR3        | All captains and the supervising staff should undergo training to learn about local dolphins and porpoises. They should be trained to be aware of the protocol for dolphin friendly“ vessel operation (refer to the Code of Conduct for Dolphin Watching Activities from AFCD).   | Protection of CWD   | Contractor           | All marine constructi on sites | Construction stage   | <ul style="list-style-type: none"> <li>• EIA</li> <li>• Contractual requirements</li> </ul> |
| S3.3.2   | WVTR4        | Training on the requirements of the WVTRP would be provided for construction vessels’ personnel to follow, which should include the details of the normal operational routings of the construction works vessels and reporting of deviations from the normal operational routings of the construction works vessels. The training course will be given to the licensed vessel captains by the trainers before commencement of work and refreshment course will be provided every quarter.           | Protection of CWD   | Contractor           | All marine constructi on sites | Construction stage   | <ul style="list-style-type: none"> <li>• EIA</li> <li>• Contractual requirements</li> </ul> |

**Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension**

| Docum ent Ref.  | EM&A Log Ref | Recommended Mitigation Measures   | Objectives of the Recommended Measures & Main Concerns to address | Implementation Agent | Location / Timing              | Implementation Stage | Requirements and / or standards to be achieved  |
|---|--------------|---|---|----------------------|--------------------------------|----------------------|---|
| <i>Deployment of Silt Curtain(s) (Extracted from Silt Curtain Deployment Plan submitted under Condition 2.16 of the EP)</i> |              |   |   |                      |                                |                      |   |
| S4  | SCD1         | Before the start of the installation work, Qualified Ecologists with dolphin monitoring experience shall scan the exclusion zone for at least 30 minutes. If dolphins are observed in the exclusion zone, the installation work shall be delayed until the dolphins left the area.                | Protection of CWD   | Contractor           | All marine constructi on sites | Construction stage   | <ul style="list-style-type: none"> <li>• EIA</li> <li>• Contractual requirements</li> </ul> |
| S4  | SCD2         | If dolphins are observed within the exclusion zone during the installation work, the relevant part of the work shall cease until the dolphins left the area.  | Protection of CWD   | Contractor           | All marine constructi on sites | Construction stage   | <ul style="list-style-type: none"> <li>• EIA</li> <li>• Contractual requirements</li> </ul> |
| S5  | SCD3         | On-board supervisors will be assigned to check the condition of the silt curtain before commencement of works every day. An inspection checklist will be kept on site for record purpose.   | Silt Curtain Integrity  | Contractor           | All marine constructi on sites | Construction stage   | <ul style="list-style-type: none"> <li>• EIA</li> <li>• Contractual requirements</li> </ul> |
| S5  | SCD4         | For the tentative arrangement of silt curtain under adverse weather, the silt curtain will not be temporary removed during adverse weather. However, related works will be suspended immediately if silt curtain is found any damaged.  | Silt Curtain Integrity  | Contractor           | All marine constructi on sites | Construction stage   | <ul style="list-style-type: none"> <li>• EIA</li> <li>• Contractual requirements</li> </ul> |
| S5  | SCD5         | Diver inspection shall be carried out if necessary to inspect the installation and decommission of silt curtain to ensure proper installation and functioning of the silt curtain according to the design drawings. Nearby marine works will resume after repairing of the damaged silt curtains. | Silt Curtain Integrity  | Contractor           | All marine constructi on sites | Construction stage   | <ul style="list-style-type: none"> <li>• EIA</li> <li>• Contractual requirements</li> </ul> |
| S5  | SCD6         | Refuse around the silt curtain will be collected at regular intervals on a daily basis so that water behind the silt curtains will be kept free from floating debris.   | Waste Management  | Contractor           | All marine constructi on sites | Construction stage   | <ul style="list-style-type: none"> <li>• EIA</li> <li>• Contractual requirements</li> </ul> |

**Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension**

| <b>EIA Ref.</b>   | <b>EM&amp;A Log Ref</b> | <b>Recommended Mitigation Measures</b> | <b>Objectives of the Recommended Measures &amp; Main Concerns to address</b> | <b>Implementation Agent</b> | <b>Location / Timing</b> | <b>Implementation Stage</b> | <b>Requirements and / or standards to be achieved</b> |
|---|-------------------------|--|--|-----------------------------|--------------------------|-----------------------------|---|
| <i>Post-planting Monitoring and Maintenance (Details to be provided after the submission of Detailed Compensatory Woodland Planting Plan as required under EP Condition 2.22)</i> |                         |  |  |                             |                          |                             |   |



**Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension**

| <b>EIA Ref.</b>   | <b>EM&amp;A Log Ref</b> | <b>Recommended Mitigation Measures</b> | <b>Objectives of the Recommended Measures &amp; Main Concerns to address</b> | <b>Implementation Agent</b> | <b>Location / Timing</b> | <b>Implementation Stage</b> | <b>Requirements and / or standards to be achieved</b> |
|---|-------------------------|--|--|-----------------------------|--------------------------|-----------------------------|---|
| <p><i>Use of New Low Noise Road Surfacing Material(s) (Details to be provided after the submission of Plan for Review of Use of New Low Noise Road Surfacing Material(s) as required under EP Condition 2.23)</i></p> |                         |  |  |                             |                          |                             |   |

**Environmental Mitigation Implementation Schedule – Tung Chung New Town Extension**

| <b>EIA Ref.</b>   | <b>EM&amp;A Log Ref</b> | <b>Recommended Mitigation Measures</b>  | <b>Objectives of the Recommended Measures &amp; Main Concerns to address</b> | <b>Implementation Agent</b> | <b>Location / Timing</b> | <b>Implementation Stage</b> | <b>Requirements and / or standards to be achieved</b>                                      |
|---|-------------------------|---|--|-----------------------------|--------------------------|-----------------------------|--|
| <i>Follow-up actions to be taken by the Contractor and Dump Truck Drivers in case of Illegal Dumping and Landfilling of C&amp;D Materials (Extracted from Waste Management Plan submitted under Condition 2.24 of the EP)</i> |                         |   |  |                             |                          |                             |  |
| S5.4  | WM1                     | Investigation report will be prepared by the Contractor and submit to ER within 2 working days.                         | Control Performance EM&A   | Contractor                  | All construction sites   | Construction stage          | <ul style="list-style-type: none"> <li>• EP</li> <li>• Contractual requirements</li> </ul> |
| S5.4  | WM2                     | The Contractor will discuss with ER for the follow up actions (e.g. warning letter, cease operation, etc.) if required. | Control Performance EM&A   | Contractor                  | All construction sites   | Construction stage          | <ul style="list-style-type: none"> <li>• EP</li> <li>• Contractual requirements</li> </ul> |